

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6461)

-
- Set a post cor. of secs. 25, 26, 35 and 36, from which
- A W.Oak 6" dia., bears S.67½°E., 610 lks. dist.
 - A Pine 24" dia., bears N.11½°E., 738 lks. dist.
 - A Pine 20" dia., bears N.57°W., 383 lks. dist.
 - A Red Fir 18" dia., bears S.26½°W., 300 lks. dist.

Survey by Frank Cain,- For: J.F. Pefley - Chainmen: Hyman Huntley & J.M. Ledgerwood, J.O. Shoup, marker - Nov. 15, 1913 - Field Book 33 Page 18

I find no BTs standing. J.M. Ledgerwood, an old resident of this district informed me that a Pine stump in Sec. 26 is one of the original BTs and is agreeing with field notes. And a Pine in Sec. 25 which evidently had been bark marked.

- Set a Post marked, from which
- A Fir 18" dia., mkd. CS S35 Tsp 29 S R6W bears S.1°50'W., 561 lks.
 - A Fir 60" dia., mkd. CS S36 Tsp 29 S R6W bears S.60°53'E., 572 lks.
 - A Pine 40" dia., mkd. CS S25 Tsp 29 S R6W bears N.8°56'E., 738 lks.
 - A Pine 36" dia., mkd. CS S26 Tsp 29 S R6W bears N.3°45'W., 740 lks.

J.W. Cole, Deputy - For: Johnson, Conlee, & Ledgerwood - 1920 - Field Book 49 Pages 7 & 8; Vol. 3 Pgs. 77-78 and "old" corner book, Pg. 130

Set a point from stumps of old Pine designated by Joe Edgerwood as original BTs in Sec. 26. Check stump of BT in Sec. 25, stump bears as follows, with Var. 21°15'E:

- Stump of old Pine, N.56°W., 250.8 ft.
 - Stump of old Pine, N.9°45'E., 487.0 ft.
- Cain's BTs bear as follows:
- Stump of tree, Pine 40" dia., N.9°45'W., 487.0 ft.
 - Pine 40" dia., N.2°30'W., 485.0ft.
 - Fir 60" dia., S.60°45'E., 377.8 ft.
 - Fir 18" dia., S.1°15'E., 365.4 ft.
- Set an Iron pie 1½" x 36". Also a Cedar poat, 3" x 3" x 36" marked S25 T29S on NE; S26 R6W on NW; S35 CS on SW; S36 on SE.
Erect mound of rock around stake.

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set by Baker, State Highway Engineer - Wit: J.M. Ledgerwood
-April 12, 1942 - C.S. File 36/27A

Set a 4" square stake for corner scribed C.S., from which
A Fir bears S.1°40'W., 333.3 ft. distance scribed S35 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale
McFarland; John Powell - April/May 1962 - C.S. File 49/139-51

Found - 1¼" I.P. at corner.
Mound stump of Cain's 60" BT to SE.
Also Baker's SW BT, good condition.
New BTs - 8" W.Oak bears S.46°E., 223.7 ft. scribed S36 T29S
R6W CS BT.
14" W.Oak bears N.31°W., 301.8 ft. scribed S26 T29S
R6W CS BT.
10" W.Oak bears N.14°E., 446.0 ft. scribed S25 T29S
R6W CS BT.

Fd. OK by Howard Johnstone, April 1978, RM 3-12

DCSO-GIS Corner visitation - 8/19/2004 - Typed: 2/2/2011 -
C.S. File 67/33-1

Monument - BC/IP - 1.5"
Comment - (needs) rehab

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2940, surveyed June/Sept. 2019-
(DCSO records Vol. 59 Page(s) 24000)

Point for the cor. of secs. 25, 26, 35, and 36, perpetuated
by Cain, in 1913; subsequently perpetuated by Baker, in 1942;
further perpetuated by Byron, (in) 1962; from original
evidence no longer in existence; as determined at the center
of an embedded mound of stone;
from which the remains of a bearing tree mkd. by Cain
A decayed fir stump, 60" dia., bears S.59¼°E., 380.2 ft.,
with scribe marks T 6W S visible on open blaze.
and the remains of a bearing tree mkd. by Baker
A decayed fir stump, 24" dia., bears S.3°W., 333.2 ft., no
marks visible.
and the remains of the bearing trees mkd. by Byron
An oak, 22" dia., bears N.14¾°E., 449.3 ft., with a healed
blaze.
An oak, 13" dia., bears S.44½°E., 223.3 ft., with a healed
blaze.

Continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An oak, 23" dia., bears N.30½°W., 301.2 ft., with a healed blaze.
and the private property cors. set by Johnstone, in 1979
An iron rod, 5/8" dia., firmly set, projecting 10" above ground, bears S.88°00'17"E., 324.97 ft.
An iron rod, 5/8" dia., firmly set, projecting 6" above ground, bears S.1°30'26"W., 316.78 ft.
and a reference monument set by person(s) unknown
An iron pipe, 1½" dia., firmly set, with top 3" below the surface of the ground, bears S.30°09'10"E., 6.25 ft.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, in a collar of stone, with brass cap mkd.
T 29 S R 6 W
S 26 | S 25
S 35 | S 36
2019
Corner located in a large open pasture, gently sloping N.45°W.