

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6463)

-----  
Set ¼ sec. post, from which  
A laurel 6" dia., bears S.73½°E., 22 lks. dist.  
A Laurel 4" dia., bears N.56°W., 15 lks. dist.

Survey by John Markham, Jr. - For: Stomar Lumber Co. - Wit: Wm. and Geo. Vaughn - March 17 & 18, 1951 - C.S. File 40/294

-----  
Set by proportionate measurement.  
At mid-point of section line, I Set a 1"x 4" Iron pipe, from which  
A Laurel 6" dia., bears N.83°W., 18.6 ft. dist. marked ¼ S, S23 T29S R6W 2880 BT.  
A Laurel 6" dia., bears S.61°E., 30.5 ft. dist. marked ¼ S, S24 BT.

Douglas Co. Surveyors Office - James W. Bryon, Deputy - Dale McFarland & John Powell, Crew - April 1962 - C.S. 49/139-50

-----  
Found - 1" I.P. at cor. and now 8" Laurel S.61°E., 30.5 ft., now snag, shows good bark scribing "¼S". I do not find Markham's NE BT.  
New BTs -12" R.Fir bears S.16°W., 14.7 ft scribed ¼ S23 CS BT  
23" R.Fir bears N.3°E., 79.0 ft. scribed ¼ S24 CS BT

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 24006-7)

-----  
The ¼ sec. cor. of Secs. 23 & 24, reestablished by proportionate measurement by Markham Jr. in 1951; perpetuated by Byron, in 1962. There is no remaining evidence of the original cor. and this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron pipe, 1" dia., firmly set, projecting 6" above ground.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd.

T 29 S R 6 W

¼

S 23 | S 24

2019

and new bearing trees

A fir, 6" dia., bears N.51½°E., 23.1 ft., mkd. ¼ S24 BT.

A fir, 21" dia., bears N.46¾°W., 27.1 ft., mkd. ¼ S23 BT.

Corner is located alongside a fence cor., with wire fences extending N., S., and W. \_\_\_\_\_