

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6463)

-----  
Set post, cor. of secs. 13, 14, 23 and 24, from which  
A B.Oak 36" dia., bears S.10°E., 50 lks. dist.  
A W.Oak 4" dia., bears N.57°E., 70 lks. dist.  
A W.oak 4" dia., bears N.8°W., 73 lks. dist.  
A Laurel 16" dia., bears S.43°W., 182 lks. dist.

F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk; Fred Smith and L.N. Sargisson - May 1919 - F.B. 46 Pgs. 47-57; Vol. 3 Pgs. 62-64 and "old" cor. book, Pg. 129

-----  
Renewed from old BTs. I set a 1½" x 30" I.P. for corner from which  
A 6" W.Oak bears S.84 3/4°E., 11 lks. C.S.B.T.  
A 4" W.Oak bears N.52¼°E., 8 lks. C.S.B.T.  
A 8" W.Oak bears N.42°W., 21 lks. C.S.B.T.  
A 6" Fir bears S.58¼°W., 14 lks. C.S.B.T.

Douglas Co. Surveyors Office - James Byron, Deputy - June 24, 1957 - C.S. File 47/195

-----  
Found all BTs and 1¼" I.P. as recorded by Frear, 1919. All trees dead except 6" Fir, now 12", S.58¼°W., 9.3 ft. which is alive and in good condition. I do not open.  
Blaze and scribe new trees:  
12" R.Fir N.6°W., 15.8 ft. scribed T29S R6W S14 CS BT.  
6" W.Oak N.58½°E., 12.7 ft. scribed T29S R6W S13 CS BT.  
6" R.Fir S.57°E., 16.2 ft. scribed S24 CS BT.

DCSO-GIS Corner visitation - 8/19/2004 - Typed: 2/2/2011 - C.S. File 67/33-1

-----  
Monument - BC/IP - 1.0"  
Comment - (needs) rehab

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 24007-8)

-----  
The cor. of secs. 13, 14, 23, & 24, perpetuated by Frear, in 1919; subsequently perpetuated by Byron, in 1957; monumented with an iron pipe, 1¼" dia., firmly set, projecting 4" above ground;  
from which the remains of an original bearing tree

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole bears S.10°E., 33.0 ft., alongside of which is a down decayed oak, size indeterminate, no marks visible.

and a bearing tree mkd. by Frear

A fir, 24" dia., bears S.65¼°W., 9.1 ft., with a healed blaze.

and a bearing tree mkd. by Byron

An oak, 12" dia., bears N.55¼°E., 11.7 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, directly over the iron pipe, with brass cap mkd.

T 29 S R 6 W

S 14 | S 13

S 23 | S 24

2019

and new bearing trees

A fir, 4" dia., bears S.13¼°E., 23.5 ft., mkd. X BT.

An oak, 17" dia., bears N.31¼°W., 38.7 ft., mkd. T29S R6W S14 BT.

Corner is located alongside a fence cor., with wire fences extending N., E., and S.

NAD 1983 (2011)

Latitude: 43°02'27.34" N. Longitude: 123°21'57.70" W.