

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6464)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears S.38°W., 56 lks. dist.
A B.Oak 20" dia., bears S.45°E., 83 lks. dist.

F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk; Fred Smith; L.N. Sargisson - May 1919 - F.B. 46 Pgs. 47-57; Vol. 3 Pgs. 62-64 and "old" cor. book, Pg. 129

Set a 3/4" x 36" Iron rod, from which
A 28" B.Oak bears N.83°W., 61½ lks. C.S.B.T.
A 20" W.Oak bears S.78°E., 64½ lks. C.S.B.T.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland and John Powell, Crew - April 1962 - C.S. File 49/139-49

Found - Both BTs as recorded by Frear, now down.
NW BT shows good reverse scribing.
Find 3/4" I.Rod at corner and under N-S fence.
New BTs -7" W.Oak bears S.58°E., 52.9 ft. scribed ¼ S13 CSBT
7" W.Oak bears S.2°W., 55.8 ft. scribed ¼ S14 CS BT.