

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6464-65)

Set post for cor. of secs. 1, 12, 13, 14, from which
An Ash 8" dia., bears N.75°E., 327 lks. dist.
A W.Oak 20" dia., bears S.55°E., 480 lks. dist.
A W.oak 18" dia., bears N.8°W., 750 lks. dist.
A W.oak 12" dia., bears S.87°W., 39 lks. dist.

F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk; Fred Smith and L.N. Sargisson - May 1919 - F.B. 46 Pgs. 47-57; Vol. 3 Pgs. 62-64 and "old" cor. book, Pg. 129

I renew as per old BTs by setting a 3/4" x 36" iron bar, from which
An 8" W.Oak bears N.48½°W., 1.205 chs. C.S.B.T.
A 30" W.Oak bears N.8°W., 7.50 chs. Old BT.
A 30" W.oak bears S.73½°W., 0.39 chs. Old BT.
A 40" W.Oak bears S.52p°E., 4.00 chs. Old BT.

Douglas Co. Surveyors Office - James W. Bryon, Deputy - Dale McFarland and John Powell, Crew - April 1962 - C.S. File 49/139-45

Found - 1½" I.Pipe at corner 1.0ft. West of North-South fence.
Orig. 30" now 32" triple W.Oak S.73½°W., 25.7ft. shows old scribing.
Orig. SE BT, now snag.
Orig. N.8°W., BT, standing.
Also find Cain's N.48½°W., 79.2 ft. now 16" W.Oak, shows scribing.
New BT - 11" W.Oak bears S.5°E., 56.4 ft. scribed.
Rescribed - O.B.T., now 32" W.Oak S.73½°W., 25.7ft. T29S R6W S14 CS BT.
Now 16" W.Oak N.48°W., 79.2 ft. mkd. S11 T29S R6W CS BT.

Fd. OK, by Burt Holt, April 1988, M 105-80
Fd. Ok by R.Brown, 1/97, M 124-38 A & B.

DCSO-GIS Corner visitation - 8/19/2004 - Typed: 2/2/2011 - C.S. File 67/33-1

Monument - BC/IP - 1.5"
Comment - (needs) rehab

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Garrett McGraw - Feb. 25, 2011 - C.S. File 67/33-13

Found - At a position indicated by OBTs fd in 1919 renewal we find a 1½" I.D. iron pipe with a 2" tall machined collar at its top. Monument is plumb and firmly set protruding 6" above ground. Probing center of fd pipe gives good evidence that ¾" iron rod is set at its center and approx 8" lower than its top (1919 record calls for a ¾"x36" iron bar monument) Monument is 1 ft. west from a North-South fence.

A W.Oak 18" dia., now a 42" DBH W.Oak with no visible marks bears N.8°W., 495.0 ft.(as per orig. rec.) Orig.

A W.Oak 12" dia., now a 54" DBH triple trunk W.Oak with a fully healed reblaze from the 1962 rescribing (on most northerly trunk) The center of root crown of this tree bears S.87°W., 25.7 ft. (as per orig. rec) Orig.

An 8" W.Oak now a 28" DBH W.Oak with a fully healed double blaze, bears N.48½°W., 79.2 ft. (as per rec.) 1919

BT from 1962 is missing; a more recent farm rd passes through the record position.

New - A 19" DBH Oregon Ash marked "T29S R6W S13 CS" "BT" on a double blaze; bears S.84°E., 135.5 ft.

Note - Monument is near bottom of gentle east facing slope on west edge of broad shallow north running valley.

See sketch in file.

Decl. 15¾°E.

Fd as per record M178-60 (surveyed 11/2020 - recorded 1/2023) by A. DeGroot