

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6466)

-----  
Set sec. cor. post for secs. 1, 2, 11 and 12, from which  
A B.Oak 15" dia., bears N.50°W., 38 lks. dist.  
A B.Oak 6" dia., bears S.65°W., 62 lks. dist.  
A W.oak 8" dia., bears N.15°E., 62 lks. dist.  
A W.oak 8" dia., bears S.24°E., 113 lks. dist.

Survey by Frank Cain - For: Riter and Moore - 1911 - F.B. 57  
Pg. 75 and "old" cor. book, Pg. 194

-----  
Reestablished. Found B.Oak stump marked BT facing NE.  
Recognized as BT described S.65°W., 62 lks. Other trees  
obliterated. Measured N.65°E., 62 lks. and Set stake marked  
C.S. Buried 1¼" x 6" x 8" Iron plate. Marked:  
A W.Oak 14" dia., N.71°15'W., 182 lks.  
A W.Oak 32" dia., S.53°30'W., 454 lks.  
A B.Oak 32" dia., S.6°00'E., 375 lks.  
A B.Oak 22" dia., N.18°30'E., 342 lks.