

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36 & S 1, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6457)

Set 1/4 sec. post, at proper dist., from which
A Pine 30" dia., bears N.40°W., 14 lks.
A W.Oak 5" dia., bears S.75°E., 50 lks.

Ben B. Irving, D.C.S. - Wit: N.E. Richardson; Allen Moore -
For: Marks and Wollenberg - April/May 1929 - C.S. File 1/65;
M 1-61; Vol. 3 Pgs. 294-96

Set on North line of sec. 1 and in position to bear out
facing of an original BT.
Drove a 3/4" x 36" Galv. I.Pipe, from which
A W.Oak 16" dia., bears N.15°38'W., 84 lks., blazed and
scribed "1/4S BT" (Orig. BT)
A W.Oak 8" dia., bears N.86°12'W., 71 lks. blazed and
scribed "1/4S CS BT."

Doug. County Surveyors Office - James W. Byron, Deputy and
crew - April 25, 1962 - C.S. File 49/139-52

Found - 3/4" I.P. at corner and 3" under surface & under N-S
fence
Find both BTs as recorded by B.B.I., 1929. 16" now
22" W.Oak N.15 1/4°W., 55.4 ft. shows good scribing.
Set Brass cap alongside cor. I.P. & mkd: 1/4 S36 T29S R6W
County Surveyors Office 1962 S 1 T30S
Rescribe, now 22" W.Oak N.15 1/2°W., 55.4 ft. "1/4 S36 CS BT".
Rescribe, now 10" W.Oak, West, 46.0 ft., not N.86°W., 46.9
ft., "1/4 S1 CS BT".

M. Heimbürger found 3/4" iron pipe with brass cap alongside.
Aug. 2001 - M138-54

Fd. BC by G. Lang, 2/2013 - M164-69