

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6462)

-----  
Set ¼ sec. post at average dist, from which  
A Laurel 6" dia., bears N.80°W., 30 lks. dist.  
A Laurel 4" dia., bears S.52°W., 18 lks. dist.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - April 1978 - RM 3-12

-----  
Set at midpoint, 5/8" x 30" Iron rod and alum. cap.  
New BTs -6" Fir N.6°W., 27.2 ft.  
5" Fir S.87°E., 5.0 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 23998-9)

-----  
The ¼ sec. cor. of secs. 25 and 36, reestablished by proportionate measurement by Johnstone, in 1978; there is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 9" above ground, with an aluminum cap mkd. T29S R6W 25 ¼ 36 LS 498 1978,

from which the bearing trees mkd. by Johnstone  
A fir, 16" dia., bears S.87°E., 5.1 ft., with a healed blaze.

A fir, 17" dia., bears N.9°W., 27.2 ft., with a healed blaze.

At the corner point Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.

T29S R6W  
¼  $\frac{S 25}{S 36}$   
2019