

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6463)

-----  
Set ¼ sec. post at average dist., from which  
A Laurel 10" dia., bears N.21½°E., 10 lks. dist.  
A Laurel 8" dia., bears S.30°E., 10 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -  
Wit: Geo. & Wm. Vaughn - Dec. 29, 1950 and Jan. 14, 1951 -  
C.S. File 40/294

-----  
Determined by O.B.T., a Laurel 16" dia., bears S.30°E. 6.6  
ft. dist. Remark ¼ S25 T29S R6W 2880 BT.  
At corner point Set 4" x 4" x 30" Oak post scribed, from  
which  
A Laurel 11" dia., bears N.43°W., 12.0 ft. mkd. ¼ S24 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - June  
24, 1957 - C.S. File 47/195

-----  
Corner renewed by Markham BTs as renewed in 1951, poor  
condition, bark scribed.

Set an iron post with brass cap mkd: County Surveyors Office  
T 29 S R 6 W  
¼  $\frac{S\ 24}{S\ 25}$   
1957

from which  
15" Fir S.18½°W., 26.8 ft. mkd: ¼ S25 CS BT.  
10" Fir N.56°E., 33.1 ft. mkd: ¼ S24 CS BT.

Douglas Co. Surveyors Office - Vernon Tracy and Crew - Aug.  
21, 1964 - C.S. File 49/139-112

-----  
Found - 1" I.P. and brass cap, dated 1957 and mkd. County  
Surveyors Office and one standing BT:  
10" now 11" D.Fir N.56°E., 33.1 ft.  
Other BT recorded, down.  
New BT - 14" D.Fir S.52°W., 39.1 ft. mkd. ¼ S25 CS BT.

Fd. Brass cap & 2 BTs by H. Johnstone, 4/1978 - RM3-12

DCSO-GIS Corner visitation - 3/8/2004 - Typed: 2/2/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP - 1.25"  
Comment - needs rehab

cont.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Garrett McGraw - 3/1/2011 - C.S. File 67/33-18

-----  
Found - 1" IP w/2½" DCSO BC (properly mkd), dated 1957, protruding 16", beneath an East-West fence line. Orig. 8" laurel now 29" bears S.30°E., 6.6 ft. (as per rec.) with previous reblaze now rehealed.  
No evidence of orig. 10" BT  
1950 11" laurel now 27" bears N.43°W., 12 ft. blaze not evident.  
1957 10" fir now 12", 7 ft. high stump fully healed double blaze (FHDB) bears N.56°E., 33.1 ft. (as per rec)  
No evidence of 15" Fir. (1957)  
No evidence of 14" D.Fir fd. (1964)  
New - A 11" DBH W.Oak scribed "¼ S24 CS" "BT" on double blaze, bears N.72¼°E., 47.8 ft.  
A 12" DBH D.Fir scribed "¼ S25 CS" "BT" on a double blaze; bears S.28½°W., 57.7 ft.  
Note - Monument is on a flat bench with a conifer and deciduous forest.  
Decl. 15¾°E.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 24005-6)

-----  
The ¼ sec. cor. of secs. 24 & 25, perpetuated by Markham Jr., in 1950; subsequently perpetuated by Byron, in 1957; further perpetuated by Douglas Co. Surveyor's Office, in 1964; further perpetuated by Smith, in 2011, under; monumented with an iron post, 1" dia., firmly set, projecting 17" above ground, with a brass cap (properly) mkd.  
from which an original bearing tree  
A madrone, 32" dia., bears S.30°E., 6.6 ft., with a healed blaze.  
and a bearing tree mkd. by Markham Jr.  
A madrone, 31" dia., bears N.42¼°W., 11.7 ft., with a healed blaze.  
and the remains of the bearing trees mkd. by Byron  
A decayed fir snag, 12" dia., bears N.55½°E., 33.3 ft., with a healed blaze.  
A decayed fir stump, size indeterminate, bears S.17¾°W., 26.0 ft., with a healed blaze.  
and the remains of a BT mkd. by Douglas Co. Surveyor's Office  
A hollowed, decayed fir stump, 12" dia., bears S.52½°W., 39.5 ft., with axe marks visible on bark.

Continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the bearing trees mkd. by Smith  
An oak, 11" dia., bears N.69¼°E., 47.9 ft., with illegible  
scribe marks visible on partially healed double blaze.  
A fir, 14" dia., bears S.29¼°W., 57.2 ft., with a healed  
blaze.  
Corner is located W., 28 ft., of fence cor., with wire fences  
extending N.45°E., E. and W.