

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6464)</p> <p>-----</p> <p>Set ¼ sec. post, at average dist., from which A B.Oak 16" dia., bears S.36°W., 37 lks. dist. A B.Oak 6" dia., bears N.67½°E., 40 lks. dist.</p>
<p>Survey by John Markham, Jr. - For: Stomar Lumber Co. - Wit: Geo. Vaughn - Aug. 14, 1951 - C.S. File 40/363-5</p> <p>-----</p> <p>As set by proportional measurement. At mid-point on Sec. line, I Set 1" x 30" Iron pipe, from which A Fir 40" dia., bears N.15°E., 6.5 ft. mkd. ¼ S BT. A Cedar 36" dia., bears S.9°E., 28.5 ft. mkd. ¼ S BT.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - June 24, 1957 - C.S. File 47/195</p> <p>-----</p> <p>Position of corner located by retracing the North line of Sec. 24. ¼ Cor. set at mid-point on true line betw. section corners. Set I.Pipe with brass cap at cor. point mkd: ¼ Cor 13,24 T29S R6W County Surveyors Office 1957, from which 36" Cedar bears S.27°E., 12.3 ft. scribed ¼ S24 CS BT. 40" Fir stump bears N.8°E., 24.2 ft. scribed ¼ S13 CS BT</p>
<p>Douglas Co. Surveyors Office - Vernon Tracy and Crew - Aug. 1964 - C.S. File 49/139-111</p> <p>-----</p> <p>Found - 1" I.Pipe and brass cap mkd: County Surveyors Office 1957, and BT stump as recorded. 40" Fir stump N.8°E., 24.2 ft. New BTs -14" Maple N.13°E., 43.0 ft. mkd. ¼ S13 CS BT. 12" Maple S.19°E., 72.1 ft. mkd. ¼ S24 CS BT. This corner lies on West edge of cat road approx. 75.0 ft. West of small creek.</p>
<p> </p>