

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec Cor 25, & 36; 30, 31 T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6421 & 6422)

Set a post for cor. to secs. 25, 30, 31, & 36 from which
Red Fir, 10" dia., bears S.60°W., 17 lks.
Red Fir, 6" dia., bears N.55°W., 27 lks.
Red Fir, 6" dia., bears N.70°E., 7 lks.
Red Fir, 8" dia., bears S.75°E., 25 lks.

Doug. County Surveyors Office - Ben B. Irving, Deputy - Aug. 21, 1929 - Witnesses H.C. Baird , F.E. Weaver - C.S. File 1/65B; Field Notes Page 82 - Vol. 3 Pg 294 - M 1-61.

Location identified from C.S. post and one BT set by Deputy County Surveyor Roberts some 20 years ago but not recorded. Renewed by setting a 4" yewwood post with 3/4"x36" galvanized Iron Pipe driven along side.
New BTs - Fir 36" dia. S.73¼°E., 82 lks. blazed and scribed
T29S R5W S31 C.S.B.T.
Fir 28" dia. S.24°W., 129 lks. blazed and scribed
T29S R6W S36 C.S.B.T.
Fir 40" dia. N.13¼°E., 118 lks. blazed and scribed
T29S R5W S30 C.S.B.T.
Fir 36" dia. N.67½°W., 64 lks. blazed and scribed
T29S R6W S25 C.S.B.T.

Doug. County Surveyors Office - James W. Byron, Deputy - and Crew - April 30, 1962 - C.S. 49/139-53

Found - 3/4" I.P. at corner.
Orig. 10" now 38" Fir S.60°W., 11.2', shows scribing on old face. Also find stump of B.B.I. NE BT now down.
SW BT, NW BT, & SE BT of B.B.I. OK, bark scribed.
New BTs - 6" R. Fir bears N.7°E. 15.5' scribed S30 CS BT.
9" R. Fir bears S.81°E. 26.2' scribed S31 T29S R5W.

Doug. County Surveyors Office - R.B. Kimberling - F.C. Silagy - 12/12/1977 - C.S. File 59/42-29 - C.S. File 59/49 - M 68-47

Found - 3/4"x34" galv. I.P. 25" in the ground.
10" now 38" W. Fir bears S.60°W., 11.2' with visible scribing "S31--S in opened blaze. (OBT).
36" now 40" D.Fir bears S.73¼°E. 55.5' (rec. 54.1') with visible bark scribing "T29S R5W S31 CS" and carved "K" on NW face. (Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 36; 30, 31 T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

36" now 34" D.Fir bears N.67½°W., 42.2' with visible bark scribing "T29S R6W S25 CS BT"
6" now 8" W. Fir bears N.7°E., 15.5' with a well healed double blaze.
9" now 14" W. Fir bears S.78½°E., (rec. S.81°E.) 26.2' with a well healed double blaze.
Set - A 1"x36" I.P. with brass cap set 5" above ground, mkd: "Douglas County Surveyor" 1977

		T 29 S	
R	S 25	S 30	R
6	S 36	S 31	5
W			W

Set - 3/4"x34" I.P. at N edge of brass cap 24" in the ground.
No new accessories. Corner is south 1.2' of an E-W fence, due west 64.2' of a 30" Fir stump which is a fence corner, fence to north & E-W and the SW cor. of clearcut unit.

Burton W. Holt , L.S. #418 - For: Sun Studs, Inc. - Gary Angiolet - Aug. 7, 1985 - C.S. File 63/8-20

Found - 1977 County brass cap with a 1" iron pipe along side of pipe with brass cap.
38" W. Fir stump which bears S.60°W., 11.2' scribe visible.
40" Fir stump bearing S.73¼°E. 55.5' scribes visible
34" Fir stump bearing N.67½°W. 42.2'. This stump cut too low for any scribing to remain.
All other bearing trees were destroyed in logging. Also the 30" fir stump 64.2' east is gone.
New BTs -10" W.Fir bears N.67°E. 38.4'mkd, T29S R5W S30 BT
6" Fir bears N.52°W., 74.4' mkd, T29S R6W S25 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2940, surveyed June/Sept. 2019- (DCSO records Vol. 59 Page(s) 23992-3)

The cor. of secs. 25, 30, 31, and 36, perpetuated by Irving, in 1929; subsequently perpetuated by Ingram, in 1977; further perpetuated by Holt, in 1985; monumented with an iron post, 1" dia., firmly set, projecting 1" above ground, with a brass cap (properly) mkd.
from which the remains of an original bearing tree
A tin-capped, decayed fir stump, size indeterminate, bears S.60°W., 11.2 ft., no marks visible.
and the remains of the bearing trees mkd. by Irving
A fir stump, 42" dia., bears N.15°E., 79.3 ft., no marks visible.
Continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25, & 36; 30, 31 T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A tin-capped fir stump, 40" dia., bears S.72¾°E., 53.6 ft., with a healed blaze.
A fir stump, 24" dia., bears N.67°W., 42.8 ft., no marks visible.
and the remains of the bearing tree mkd. by Holt
A decayed fir stump, size indeterminate, bears N.62¾°E., 38.9 ft., no marks visible.
and new bearing trees
A cedar, 6" dia., bears N.73¾°E., 12.7 ft., mkd. T29S R5W S30 BT.
A fir, 7" dia., bears S.71½°E., 10.6 ft., mkd. T29S R5W S31 BT.
A cedar, 4" dia., bears S.58°W., 31.4 ft., mkd. X BT.
A fir, 7" dia., bears N.79¾°W., 19.5 ft., mkd. T29S R6W S25 BT.
Corner is located alongside a fence cor., with wire fences extending N., S., E., and W.