

PRIMARY CORNER DESCRIPTION Sec. Cor 13 & 24; 18 & 19 T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6420)

Set a post for secs. 13, 18, 19, & 24, from which
B. Oak, 12" dia., bears S.85°W., 85 lks.
B. Oak, 10" dia., bears N.15°W., 106 lks.
B. Oak, 12" dia., bears N.10°E., 194 lks.
Laurel, 12" dia., bears S.85°E., 100 lks.

John Markham, Jr., Eng. - George Vaughn, Witness - For -
Stomar Lbr. Co. - 8-7-51 - C. S. File 40/363-1

As determined by old bearing trees.
30" W. Oak, bears S.85°W., 46.0', standing.
12" B. Oak, bears N.15°W., 69.0', dead.
30" B. Oak, bears N.9°E., 128.0', fallen.
At corner point set stone and Iron Pipe from which
30" W. Oak, bears S.85°W., 46.0'. I remarked this old
bearing tree S24, BT.
36" W. Oak, bears N. 83°W., 76.0', marked S13 BT.
36" B. Oak, bears North 71.5', marked S18 BT.
18" B. Oak, bears S.16°E., 133', marked S19 BT.
There are old fences running N-S-E-W from this corner.

Doug. Co Surveyors Office - James Byron, Deputy - D.McFarland &
J.Powell - 2/1962 - C.S. 49/64-63 (1954 report C.S. 46/63 (PG 6)

Found - Orig. 12", now 44" B.Oak, opened years ago, center
rotted, S.85°W. 45.0', not 56.1'.
1" I.P. at corner & remains of NE & NW Orig. BT's
show axe work, check record.
Note - N.S. & fence to West corner bears S.25°E., 4'.
New BTs - 40" B. Oak, bears N.0½°E., 72.8', scribed S18 T29S
R5W CS BT. (This BT previously bark scribed)
48" B.Oak bears N.82°W. 75.0', previously scribed.
44" B.Oak, O.B.T. S.85°W., 45'. We Scribe CS BT,
(previously bark scribed)
W. Oak, bears S.15°E. 134.4'. We scribe CS BT.

Doug. County Surveyors Office - R.B. Kimberling - F.C. Silagy
- Dec. 14, 1977 - C.S. File 59/42-32

Found - A 1"x27" Iron Pipe.
A 12" now 44" B.Oak, bears S.85°W., 46.1' (rec
56.1') with a chopped open blaze, 12" center
rotted away and another well healed double blaze
at the left side of chopping.

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor 13 & 24; 18 & 19 T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 40" B.Oak, bears N.0 ½°E., 72.8' with scribe marks visible in an almost healed double blaze.
A 48" B.Oak, bears N.82°W. 75.0' with a well healed blaze.
A 24" W. Oak, bears S.15°E., 134.4' with a well healed blaze.
Set - A 1"x36" I.P. with brass cap set 6" above ground mkd:
"Douglas County Surveyor"
T 29 S
R6 S 13 | S18 R5
S 24 | S19
1977
I set the I.P. at the N. edge of the brass cap.
No new accessories. Corner is at S.W. edge of a 7 ft. high fence post, 8 ft. N.W. of a fence corner to the west and N-S.

DCSO-GIS Corner visitation - 8/20/2004 - Typed: 2/2/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - (needs) rehab

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Garrett McGraw - March 3, 2011 - C.S. File 67/33-21

Found - A 2 5/8" dia., (1977) brass cap (properly mkd) on a 1 1/2" I.D. iron pipe, firmly set and protruding 3" above ground. Iron pipe frm 1951 renewal said to be on north edge of BC, monument is not found.
BC monument is on south edge of 5.5 ft. tall fence corner post with fences now running north-south and west.
Possible evidence of two orig. 1854 BTs:
A B.Oak 12" dia., now an approx. 10" tall rotted barkless 38" DBH Oak stump with a rotted & burned center but showing a previous blaze search opening; bears S.85°W., 46.0 ft. (agrees with 1951, 1962 & 1977 reasonably well)
A B.Oak 12" dia., now a root depression with rotted Oak remnants, bears N.10°E., 128.0 ft. (as per orig. rec)
A 36" W.Oak now a 9 ft. long, 40" dia., fallen & cut B.Oak stump (face side down) the center of root crown of which bears N.78°W., 76.0 ft. (rec. N.83°W., 76.0) 1951

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor 13 & 24; 18 & 19 T29-5

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 36" B.Oak now a 46" DBH B.Oak with a nearly fully healed single blaze; bears North 73.0 ft. (rec. North 71.5' is a good face measurement) 1951

An 18" B.Oak now a 33" DBH W.Oak with a fully healed single blaze bears S.15°E., 133.0 ft. (1951 rec. S.16°E. 13.3') 1951

New - A 10" DBH D.Fir scribed "T29S R6W S13 CS" "BT" on a double blaze; bears N.35°W., 52.3 ft.

Note - Monument is on west edge of large open pasture near foot of gentle wooded easterly slope and north from an east west running swale.
Decl. 15¾°E.