

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; 6 T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6419)</p> <p>-----</p> <p>Set quarter section post, from which Ash, 15" diam., bears S.15°W., 235 lks. Ash, 12" diam., bears N.67°E., 214 lks.</p>
<p>Wm. S. Barnes - For: Otis Clayton - Nov. 1969 - C.S. File 55/136; M 33-63</p> <p>-----</p> <p>Prorated corner. Set - Brass Cap Mkd: Eng. #2128 Nov. 1969, 1/4 Cor. T29S R6W Sec. 1, T29S R5W Sec. 6. New BT - 24" Forked Ash by creek, N.89°E. 162.4' mkd: "1/4 S6 BT"</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/7/2009 - C.S. File 67/28-1</p> <p>-----</p> <p>Found - 1969 2½" brass cap on a 1½" O.D. iron pipe protruding 12" out of ground. Brass cap is orientated westerly. 4½ ft high wood power pole is 1 ft westerly of BC/IP 24" now 29" dia., forked Ash with a partially healed double blaze with scribing visible "9R6" bears N.89°E., 162.4 ft. (agrees with rec.) 1969</p> <p>New - 3/4" IP 1" underground bears S.2½°W., 155.2 ft. 3/4" IP 4" underground bears S.19°E., 125.5 ft. Power pole No. "PPL 29-05 060401" bears S.1°W., 155.2 ft. SE corner of barn bears N.49°W., 61.1 ft.</p> <p>Note - Compass decl. 16¼°E. (See Sketch in file.)</p>
<p>DCSO-GIS Corner visitation - 8/24/2004 - Typed: 2/2/2011 - C.S. File 67/33-1</p> <p>-----</p> <p>Monument - BC/IP 1.25" Comment - (needs) rehab</p>
<p>Fd. BC 8/2021 - M Heimburger - M179-74</p>
<p> </p>