

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 037020

PRIMARY CORNER DESCRIPTION SE Cor. McCullough DLC #37

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |

Original - Bowman and Burnett, under Contract dated Sept. 1855

Set a Post as per instructions from which
A B.Oak 8" dia., bears N.55°W., 162 lks.

G.G. Stewart - Wit: Harold Nichols; J.C. Cabot; S. McBee; C. Crocker; W.H. Coats - Nov. 8, 1922 - Vol. 3 Pg. 129 and "old" corner book, Pg. 133

Drove an Iron bar.
Found - Stump of original BT but stump had been moved. Set as per fence line and witnesses, checked with exterior NE corner. Marked:
A 9" W.Oak N.85½°W., 42.3 ft.
S.55°E., 168.3 ft.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5902)

Intersect the SE. cor. of Claim No. 37, which is an iron pipe 1" dia., 6" above ground, set by county surveyor from the original bearing tree, all evidence of which is now entirely obliterated. I designate this cor., Cor. No. 4.
From the cor.:
A W.Oak 10" dia., bears S.55°E., 255 lks. dist., mkd. D L C 37 C S B T.
A W.Oak 10" dia., bears N.87½°W., 64 lks. dist., mkd. A P 4 D L C 37 B T.