

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 045020

PRIMARY CORNER DESCRIPTION Int. SW Cor. Craxton DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett, under Contract dated Sept. 1855

-----  
Set a post, from which  
A B.Oak 18" dia., bears N.80°E., 14 lks.  
A B.Oak 12" dia., bears S.85°W., 48 lks

Douglas Co. Surveyors Office - Ben B. Irving - Jim Byron; Ray Irving - Work done by request of County Court for Road Survey Rd. #38 - 1954 - C.S. File 46/36

-----  
Corner renewed from old BTs:  
A 36" B.Oak N.80°E., 14 lks., standing but center rotted out.  
Stump of 24" B.Oak S.85°W., standing with center rotted out.  
Both check for bearings and distances. Also within 10 ft. of fence corner.  
Set a 5/8" x 30" Iron rod for corner.  
Blazed and scribed two new trees:  
Red Fir 12" dia., N.51°W., 12.2' mkd. Int. L. Cl 45 CS BT.  
Red Fir 18" dia., bears S.5°W., 51.0 ft. mkd. SW Int. L Cl 45 CS BT.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause March 28, 1995 - C.S. 64/58-7

-----  
Found - 5/8" I.R. flush with ground (1954 DCS0)  
18" Now 43" dia. B.Oak, with a fully healed blaze, bears N.80°E., 9.2' (agrees w/ rec.) 0BT.  
12" now 24" dia. 6' high D.Fir stump with a fully healed blaze, bears N.51°W., 12.2' (agrees w/ rec.) 1954 DCS0.  
18" now 34" dia. 2' high D.Fir stump with evidence of a healed lower blaze, bears S.5°W., 51' (agrees w/ rec.) 1954 DCS0.  
(Note: BT's to be removed in near future)  
Set - 5/8" I.R. at corner if referenced, measured 27" long, a 2 3/8" dia. Brass cap on 1 3/8" O.D. by 32" long I.P. is set at referenced position. Top is 12" below ground. 5/8" i.r. is set along north edge of BC/IP 14" below ground.  
New - 5/8" I.R. with yellow plastic cap mkd. "Hibbs PLS 2234", bears N.72°E., 108.8', top is flush with ground.  
5/8" I.R. with yellow plastic cap mkd. "Hibbs PLS 2234", bears S.45½°W, 47.8', top is flush with ground. (Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 045020

PRIMARY CORNER DESCRIPTION Int. SW Cor. Craxton DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5/8" x 30" long I.R. with DCSO Alum. cap mkd. "B01" 1995",  
bears S.20°W., 65.3' top protrudes 3" above ground.  
5/8" x 30" long I.R. with DCSO Alum. cap mkd. "B02 1995",  
bears S.70°W., 84.3' top protrudes 3" above ground.

FD. OK, James Hibbs, Dec. 1994 - M122-48