

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 046040

PRIMARY CORNER DESCRIPTION WNW Cor. McCullough DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Bowman and Burnett, under Contract dated Sept. 1855</p> <p>-----</p> <p>Set a post, from which A Pine 14" dia., bears N.45°W., 312 lks. An Ash 14" dia., bears S.10°W., 334 lks.</p>
<p>Douglas Co. Surveyors Office - Ben B. Irving - James Byron; Ray Irving - Work done at request of County Court for road survey, Rd. #38 - 1954 - C.S. File 46/36</p> <p>-----</p> <p>Found - 2" Iron Pipe. 40" Ash, S.10°W., 334 lks. previously remarked. 20" Fir N.89°E., 121 lks. previously remarked C 46 T29S W S BT, W. fork of 3 prong tree.</p>
<p>Fd. OK, V. McLind, 1972, RM 2 - 35</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - May 1962 - C.S. File 49/139-69</p> <p>-----</p> <p>Found - 2" I.P. at corner and now 27" D.Fir stump bears N.86½°E., 121.0 ft. good scar. New BT - 21" Pine bears N.31°E., 89.4 ft. scribed W Ex L Cl 46 CS BT.</p>
<p>Douglas Co. Surveyors Office - Gary Langlitz; L.E. Monrean; K. Cheney; S. Flause - Nov. 8, 1977 - C.S. File 59/42-7</p> <p>-----</p> <p>Found - 2" I.P. firmly set and extending 5" above ground. (I.P. possibly set by Boyer in 1943, C.S. 31/15) We find no trace of the orig. bearing trees. A 3 forked D.Fir stump approx. 50" overall with good scar bears S.87°E., 121.0 ft. (Rec. N.89°E., per Irving, 1954 and N.86½°E., per Byron, 1962) A 21" now 26" P.Pine, alive and well healed located on the North edge of a graveled driveway and at the corner of fences running northerly and westerly, bears N.31°E., 89.4 ft. New BT - 12" P.Pine scribed "WNW DLC 46 CS BT" on a double blaze, bears N.53°W., 14.9 ft.</p>
<p>Douglas Co. Surveyors Office - Larry E. Monrean; S. Flause; R. Smith - June 7, 1984 - C.S. File 62/18-24</p> <p>-----</p> <p>Found - 2" I.P. firmly set and protruding 5" from ground. Pipe leans slightly north. Possible Boyer pipe, 1943. (Cont. Next Page)</p>

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 046040

PRIMARY CORNER DESCRIPTION WNW Cor. McCullough DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No trace of original BTs.  
A triple trunk D.Fir approx. 50" in overall diam. with a healed single blaze bears S.88°E., 121.0 ft. (Past records, N.89°E.; N.86½°E.; S.87°E.)  
21" dBH now a 26" DBH P.Pine with a healed double blaze is now dead, fallen and dislocated from stump hole. Stump hole bears N.31°E., 89.4 ft.  
12" DBH now 14" DBH P.Pine with a healed double blaze bears N.53°W., 14.9 ft.

New Accessories:  
A 5/8" dia. I.Rod with alum. cap marked "Douglas Co. Rd. Dpt. R/W .30", firmly set and protruding 4" from ground bears N.59 3/4°E., 91.4 ft.

Monument is located approx. 400 ft. NW of Upper Ollala Co. Rd. #38 and graveled access road to Berry Creek Dam structure (Ben B. Irving Reservoir.)

---

Fd. OK, Mark Heimbürger, April 1992, Land Partition 1992-0035  
Fd. OK by M. Luttrell, Feb. 1998 - L.P. 1998-0043  
FD. 2" IP by M. Heimbürger - 1/2007 - M146-52

---

2