

PRIMARY CORNER DESCRIPTION W.P. of ¼ sec. 31, T29-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6519)

Set ¼ sec. corner, from which,
A laurel, 10" diam., bears S.70°W., 25 lks.
A laurel, 8" diam., bears N.80°E., 10 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of Dec. 4, 1905 (DCSO Vol. 14 Page 5940-41)

Intersect the point for Ford's ¼ sec. cor. of secs. 31 & 36 located by measurement from the original bearing trees.
At the exact cor. point
Set an iron post, 3 ft. long, 1" diam., 28" in the ground, for witness point, with brass cap marked
WP
1924
from which (the original bearing trees)
A laurel, 18" diam., bears N.74°W., 25 lks. (not S.70°W.), marks are legible.
A laurel, 14" diam., bears S.80°E., 10 lks. (not N.80°E), marks are legible.
new bearing trees:
A laurel, 5" diam., bears N.51°E., 35 lks., marked WP BT
A fir, 18" diam., bears S.73°E., 32 lks., marked WP BT