

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. ¼ cor. for Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Re-establishment of corners - Fred Mensch , U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6020)

Intersect center latitudinal subdivision line of original sec. 31, T29S R7W, S. 80°56"E., 4.96 chs. from the Ford ¼ cor. of secs. 31 and 36 restored as witness point.

At the point of intersection

Set an iron post, 3 ft. long, 1" diam., 28" in the ground, for resurvey ¼ sec. cor., if sec., 31 only, T29S R7W, with brass cap marked:

|¼S31
1924

from which:

A fir, 12" diam., bears N.79°E., 28 lks., mkd ¼ S 31 BT.

A fir, 10" diam., bears S.57°E., 45 lks., mkd ¼ S 31 BT.

David Edwards - Crew: Brant Miller & Eric Sprinkle - 1/19/2017 - C.S. File 65/95-20

Found - 1924 GLO Brass capped iron pipe in good condition.
No accessories remain

New - An 11" dia., fir bears N.14°E., 6.7 ft.

A 12" dia., fir bears S.53°E., 18.0 ft.

Both scribed "¼ S31 BT"

A six ft steel post is set 2 ft north.

Compass decl. 15°E.