

PRIMARY CORNER DESCRIPTION Sec cor to 25 & 36 only; T29-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 16 Page 6571)

-----  
Set cor. secs. 30, 31, 25, & 36 from which:  
A fir, 15" diam., bears N.48°E., 31 lks.  
A fir, 6" diam., bears N.77°W., 30 lks.  
A maple, 6" diam., bears S.58°W., 55 lks.  
A maple 8" diam., bears S.26°E., 120 lks.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records, Vol. 14 Page 6019)

-----  
Intersect the point for Hathorn's cor. of secs. 25, 30, 31, 36, located by measurement from the positions of the NE and SW original bearing trees. These trees have rotted down, but blazes show on the decayed logs, and stump holes evidence their original positions. No evidence is found of the old SE and NW bearing trees

At the exact cor. point

Set an iron post, 3 ft. long, 2" diam., 28" in the ground, for cor. of secs. 25 and 36 only with brass cap marked:

T29S
S 25
S 36
R8W
1924

from which (the original bearing tree)

Stump hole of fir, bears N.48°E., 31 lks.

Stump hole of maple, bears S.58°W., 55 lks.

New bearing trees:

A fir, 48" diam., bears S.42°W., 83 lks., marked T29S R8W S36 BT.

A fir, 40" diam., bears N.59°W., 164 lks., marked T29S R8W S25 BT.

James W. Byron, Dep. Co. Surveyor - Dale McFarland and John Powell - May/June 1962 - C.S. 49/139-69

-----  
Found - Orig. 40", now 44" Fir, N.59°W., 108.2 ft., shows good scar.

Orig. SW BT down. Also find brass cap at corner & at east edge of 4 ft. down BT.

New BTs -10" Cedar, bears N.37°W., 32.5 ft., scribed S25 T29S R8W CS BT.

7" Fir, bears S.28°W., 6.5 ft., scribed S36 CS BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100143

PRIMARY CORNER DESCRIPTION Sec. cor. to 25 & 36 only T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Resurvey - Wayne L. Rogers, Cadastral Surveyor - Group # 1454 - Aug 88/May 89 (DCSO records Vol. 49 Page(s) 18735-36)

-----  
At the cor., monumented with an iron post, 1" diam., firmly set projecting 4" above ground, with brass cap mkd.

T 29 S  
S25 |  
S36 |  
R8W  
1924

from which the remains of bearing trees mkd. by Mensch  
A root hole, bears S.42°W., 83 lks., with a down decayed fir alongside, size indeterminate no marks visible.  
A root hole, bears N.59°W., 164 lks., with a down fir alongside, 45" diam., with healed blaze.  
and the remains of bearing trees mkd. by James W. Byron, 1962  
A grand fir snag, 10" diam., bears S.25°W., 10 lks. with healed double blaze.  
A cedar, 13" diam., bears N.40°W., 49 lks., with fragmentary scribe marks visible on partially healed double blaze.

No suitable tree available in sec. 36  
The corner is located in a timber corner, with timber on NW. and clearcut to NE., SE., and SW.

David Edwards - Crew: Brant Miller & Eric Sprinkle - 1/19/2017 - C.S. File 65/95-22

-----  
Found - 1924 GLO Brass capped iron pipe in good condition. 15" dia., cedar with a healed blaze from the 1962 DCS renewal bears N.40°W., 32.3 ft.  
No other BTs remain.  
New - An 8" dia., Fir scribed T29S R8W S36 BT bears S.50°W., 20.8 ft.  
A Six ft steel post is set 2 ft. south.  
Compass decl. 15°E.