

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6015)

Intersect the line bet. secs. 19 & 30, S.80°27'E., 2.24 chs. from Ford's cor. of secs. 19, 24, 25, & 30 restored as cor. #2 of tract #53.

At the point of intersection

Set an iron post, 3 ft. long, 2" diam., 28" in the ground, for resurvey cor. of secs. 19 & 30, with brass cap marked:

:T29S

:S19

:S30

R7W

1924

from which

A pine, 14" diam., bears N.32°E., 38 lks., marked T29S R7W S19 BT.

A cedar, 10" diam., bears S.55°E., 20 lks., marked T29S R7W S30 BT.

James W. Byron, Dep. Co. Surveyor - John Powell and Wm. Stoffel - July 1962 - C.S. 49/139-96

Found - Brass cap at cor. & Both BT's. NE BT. Dead. SE BT has broken top.

New BTs - 16", cedar bears S.36°E., 28.7 ft., scribed S30 T29S R7W CS BT.

We find 18", cedar bears N.52°E., 31.4 ft., previously scribed S19 T29S R7W BT.

Howard W. Johnstone - for Roseburg Lumber Co. - Feb. 11, 1963
M 24 - 62

Found - Brass cap and scribed:
A 14" I.Cedar, N.52 3/4°E., 31 ft.

FD. OK. - GLO Resurvey - Daniel E. Weller & Dale T. Bedell - Group # 1447 - June 1988/Feb 1989 (DCSO records Vol. 48 Page 18529)