

PRIMARY CORNER DESCRIPTION E. ¼ cor. to sec 24 only T29-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 16 PG. 6571)

-----  
Set ¼ sec. post, from which  
A laurel, 12" diam., bears S.81°E., 20 lks.  
A laurel, 6" diam., bears N.12°W., 30 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6015)

-----  
Intersect the point for Hathorn's ¼ sec. cor. 19 & 24, located by measurement from the original bearing trees on which the marks are legible.

At the exact cor. point  
Set an iron post 3 ft. long, 1" diam., 28" in the ground, for ¼ sec. cor. of sec. 24 only, with brass cap mkd.

¼S24  
1924

from which (the original bearing trees)  
A laurel, 20" diam., bears S.81°E., 20 lks.  
A laurel, 18" diam., bears N.12°W., 30 lks.

New bearing trees:  
A fir, 20" diam., bears S.5°W., 37 lks., marked ¼ S 24 BT  
A fir, 10" diam., bears N.69°W., 32 lks., marked ¼ S 24 BT

FD. OK. - Jan. 10, 1980 - H. Johnstone - M 81 - 75

FD. OK. - GLO Resurvey - Daniel E. Weller & Dale T. Bedell - Group # 1447 - June 1988/Feb 1989 (DCSO records Vol. 48 Page 18529)

Mark Smalley, L.S. #2354 - For: Kenneth & Hallie Ford - Dec. 1994 -M 121-51

-----  
Found - 1924 GLO brass cap & iron rod.  
24" Madrone, N.12°W., 19.8', snag.  
19" Fir, N.69°W., 21.1', healed.  
24" Madrone, S.81°E., 13.2', stump.  
34" Fir, S.5°W., 24.4', healed.  
New BTs- 14" Fir, North 13.6', "¼ S BT"  
10" Cedar, N.84°E., 21.3', "¼ S BT"