TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION West ¼ cor. of sec. 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6014)

Intersect the center latitudinal subd. line of original sec. 19, S.80°40'E., 2.23 chs. from Ford's ¼ sec. cor. of secs. 19 and 24, restored as witness point.
At point of intersection
Set an iron post, 3 ft. long, 1" diam., 28" in the ground, for resurvey ¼ sec. cor. of sec. 19 only, with brass cap mkd.
:¼S19
1924
from which
A cedar, 10" diam., bears N.31°E., 43 lks., mkd. ¼ S19 BT
A laurel, 28" diam., bears S.39°E., 78 lks., mkd. ¼ S19 BT

James W. Byron, Dep. Co. Surveyor - John Powell and Wm. Stoffel - July 1962 - C.S. 49/139-96

Found - Brass cap & SE. BT., shows scars. NE. BT. not found.
New BT -18" laurel, bears East 7.5 ft., scribed W¼ S19 CS BT.

FD. OK. - GLO Resurvey - Daniel E. Weller & Dale T. Bedell - Group #1447 - June 88/Feb 89(DCSO records Vol. 48 Page 18530)

Mark Smalley, Roseburg Forest Products - Party Chief: William Olson - Witness: Ken Coble - 6/2009 - C.S. File 65/66-48

Found - 1924 GLO Cap, properly marked.
30" Laurel S.39°E., 51.5' healed face 1924
14" Laurel East 7.5' in poor condition with partially healed face. 1962
10" cedar, N.31°E., 43 lks., 1924, gone.
New - 6" D.Fir N.8°E., 42.2' measured to nail in side center of stump, scribed "¼S19BT"
14" D.Fir S.50°E., 31.1' measured to nail in side center of stump scribed "¼S19BT"
Decl. 18°