

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION W. Sec. cor. 7 & 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6010)

Intersect the line bet. secs. 7 and 18, S.76°03'E., 2.98 chs. from Ford's cor. of secs. 7, 12, 13, & 18 restored as cor. No. 2 of tract #49.

At the point of intersection

Set an iron post, 3 ft. long, 2" diam., 28" in the ground, for resurvey cor. of secs. 7 and 18, with brass cap mkd.

:T29S

:S7

:S18

:R7W

1924

from which

A black oak, 16" diam., bears N.39°E., 8 lks., mkd. T29S R7W S7 BT.

A black oak, 24" diam., bears S.55°E., 38 lks., mkd. T29S R7W S18 BT.

James W. Byron, Dep. Co. Surveyor - John Powell and Dale McFarland - May/June 1962 - C.S. 49/139-72

Found - Brass cap at corner. NE. BT. shows scribing, now dead. SE. BT. O.K., shows good scar.

New BT:

19" R. Fir, N.49°E., 17.7ft., scribed S7 T29S R7W CS BT

GL0 Resurvey - Daniel E. Weller & Dale T. Bedell - Group #1447 - Jun88/Feb89 (DCSO records Vol. 48 Page 18530)

At the cor., monumented with an iron post, 1" diam., firmly set, projecting 10" above ground, with brass cap mkd.

| T 29 S

| S 7

| S18

| R 7 W

1924

from which the remains of the original bearing trees

An oak stump, 20" diam., bears N.39°E., 8 lks., no marks remaining.

An oak snag, 19" diam., bears S.55°E., 38 lks., no marks remaining.

and a bearing tree mkd. by James Byron, in 1962

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. cor. to 7 & 18 only

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A fir, 27" diam., bears N.49°E., 27 lks., with healed
blaze.
and a new bearing tree
A cedar, 16" diam., bears S.35¼°E., 44½ lks., mkd. T29S
R7W S18 BT.