

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION Sec. ¼ cor. to 7 W Bdy; T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6009)

Intersect the center latitudinal subdivision line of sec. 7, 1.93 chs., S.82°43'E., from Ford's ¼ sec. cor. of secs. 7 & 12, restored as witness point, heretofore described.

At the point of intersection
Set an iron post, 3 ft. long, 1" diam., 28" in the ground, for resurvey ¼ sec. cor. of sec. 7 only, T29S R7W., with brass cap marked

:¼S7
1924

from which

- A fir, 10" diam., bears N.47°E., 33 lks., marked ¼ S7 BT.
- A fir, 12" diam., bears S.47°E., 13 lks., marked ¼ S7 BT.

Surveyor - N.E. Richardson; wit. M.E. Godfrey & L.S. Kershner - July 1947 - C.S. 38/188

Found an Iron Pipe with brass cap, the O. B.T. bears N.47°E., 33 lks.

Set new bearing trees

- A Fir, 14" diam., bears N.72½°E., 30.3 ft.
- A Fir, 14" diam., bears S.50°E., 46.2 ft.

James W. Byron, Dep. Co. Surveyor - Milo Godfrey & Clete Putnam - Nov. 2, 1960 - C.S. 49/139-3

Found - Brass cap at corner & W.P. N.82°43'W., 1.93 chs. (1924) B.T.'s gone, renewed BT's., now stumps.

New BTs- 4" Laurel, bears S.22°E., 74 ft., scribed ¼ S7 CS BT
15" B. Oak, bears N.13°E., 40 ft. scribed ¼ S7 CS BT

FD. OK. - GLO-Resurvey - Daniel E. Weller & Dale T. Bedell - Group #1447 - Jun 8 1988/Feb 17 1989 (DCSO records Vol. 48 Page(s) 18532)

Found OK by D. Edwards, April 2002 - M140-16
FD. BC & 2 BTs by Ken Hoffine, 8/2007 - M154-14