

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 16 Pg. 6569)

- 
- Set post for cor. secs. 6, 7, 1 and 12, from which
- A B.Oak 12" dia., bears S.80°W., 25 lks. dist.
  - A B.Oak 10" dia., bears N.58°E., 32 lks. dist.
  - A B.Oak 10" dia., bears N.40°W., 113 lks. dist.
  - A B.oak 12" dia., bears S.42°E., 44 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6008)

-----  
Intersect the point for the hathorn cor. of secs. 1, 6, 7, and 12, located by measurement from the original bearing trees, on which the marks are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 1 and 12, with brass cap marked:

T29S	
S 1	
S 12	
R8W	
1924	

from which the original bearing trees:

- A B.oak 14" dia., bears N.51°E., 32 lks. dist.
- A B.Oak 16" dia., bears S.36°E., 44 lks. dist.
- A B.Oak 16" dia., bears S.80°W., 25 lks. dist.
- A B.Oak 14" dia., bears N.40°W., 113 lks. dist.

New Bearing trees:

- A Fir 12" dia., bears S.65°W., 14 lks. dist., marked T29S R8W S12 BT.
- A Fir 10" dia., bears N.13°W., 31 lks. dist., marked T29S R8W S1 BT.

H.L. Eppstein, C.S. - Wit: N.E. Richardson; H.Z. Ireland - March 6, 1931 - Vol. 4 Page 1

- 
- Standard govt. corner, mkd. T29S S1 and S12 R8W, from which
- A 10" Fir S.75°W., 9.6 ft.
  - An 8" Fir N.12°W., 198 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Wit: Dale McFarland; John Powell - May/June 1962 - C.S. File 49/139

-----  
Found - 1924 Brass cap and both BTs, now stumps. NW BT shows good scribing.

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100560

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -10" R.Fir bears S.21½°E., 23.3 ft. scribed S7 T29S  
R7W CS BT.  
13" B.Oak bears N.55°E., 21.4 ft. scribed S7 T29S  
R7W CS BT.  
Fences run North, South and West from corner.

Found OK by DeGroot, Jan. 1996 - Partition Plat 1996-0064  
FD. BC & 2 BTs by Ken Hoffine, 8/2007 - M154-14