

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. ¼ cor. to 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6517)

Set ¼ sec. post, from which
 A B. Oak, 10" diam., bears N.24°E., 23 lks.
 A B. Oak, 12" diam., bears S.38°W., 46 lks.
(This point now AP #3 of Tract #48, NOT a 1/4 Corner)

G.G. Stewart - Wit. Harold Nichols, J.C. Cabot, S. McBee, C. Crocker, & W.H. Coats - Nov. 8, 1922 - Vol. 3 Pg. 129

At the ¼ cor. of 6 (T29-7) & 1 (T29-8)
Drove an I.P. Original BT's gone. Set from S.W. corner of claim 37. Marked
 A 14", W. Oak, S.41½°W., 26 ft.
 A 30", W. Oak, N.85°E., 47.7 ft.
(Obsolete, see 1924 GLO survey)

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6006)

Intersect the N. bdy. of the H.O. Waters D.L.C. #43, N.89°48'W., 18.94 chs. from the NE. cor. thereof, identical with center latitudinal subdivision line of original sec. 6, S.89°48'E., 1.88 chs. from the original ¼ sec. cor. At the point of intersection
Set a basalt stone, 20x12x12", 15" in the ground, for resurvey ¼ sec. cor. of sec. 6 only, T29S R7W., marked ¼ on E. face; from which
 A W. Oak, 30" diam., bears N.26°E., 190 lks., mkd ¼ S6 BT.
 A W. Oak, 8" diam., bears S.17¼°E., 84 lks., mkd ¼ S6 BT.

James W. Byron, Dep. Co. Surveyor - John Powell & Dale McFarland - May 1962 - C.S. 49/139-73

Found- 1924 Brass cap at cor. & both BT's.
 We do not find corner stone.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/12/2001 - C.S. File 66/21-11

Found - 1924 GLO BC/IP, protrudes 9" above ground. 2 ft. North of E-W fence line.
 30" now 52" dia., W.Oak with a fully healed single blaze, bears N.26°E., 125.4 ft. (1924)
 1924 SE BT gone.

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W ¼ cor. to 6 only

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - 6" W.Fir double blazed & scribed "W ¼ S6 CS BT"
bears N.75°E., 5.9 ft.
14" dia., Ash double blazed & scribed "W ¼ S6 CS BT"
bears S.70°E., 14.0 ft.
Compass decl. 17 3/4°E.