

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Tsp. Corner (Sec 6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5746)

Set a post cor. of secs. 1, 6, 31 and 36, from which
A B.Oak 15" dia., bears N.46°W., 142 lks. dist.
A B.Oak 12" dia., bears S.45°W., 52 lks. dist.
A W.Oak 12" dia., bears N.63°E., 225 lks. dist.
A B.Oak 20" dia., bears S.21°E., 110 lks. dist.

J.W. Cole, For: J.H. Coats - Nov. 1922 - M 1-2

Set Iron pipe and remarked 4 standing O.B.T.s (Ford Tsp. Cor.)
(Pipe set by Stewart, M 3-74)

GL0 resurvey by Mensch, 1924 - (DCSO records, Vol. 14 Page 5879)

Intersect the E. bdy. of T28S R8W., 17.51 chs. N. of the Hathorn cor. of Tps. 28 and 29 S., Rs. 8 W., At the point of intersection:

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 28 and 29 S., R.7W., with brass cap mkd:

T28S
R7W
S31
S6
T29S

1924

from which

A Fir 6" dia., bears N.81°E., 62 lks. dist., mkd. T28S R7W S31 BT.

A Fir 10" dia., bears S.80½°E., 58 lks. dist. mkd. T29S R7W S6 BT.

(Orig. Ford Tsp. cor. re-established as Cor. No. 3 of Tract #63, identical with Cor. No. 2 of Tract #47, T29S R7W.)

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - April 1961 - C.S. File 49/50-46

Found Both Fir BTs recorded by Mensch. Each is now down. We open and find good scar on each BT.

Brass cap from 1924 NOT FOUND.

Set Brass cap mkd: $\frac{S31}{S6}$ T28S R7W County Surveyor's Office, 1961

New BTs -6" Cedar bears N.31½°E., 82.7 ft. scribed S31 T28S R7W CS BT. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION NW Tsp. Cor. (Sec. 6)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

12" R.Fir bears S.28½°E., 99.7 ft. scribed S6 T29S
R7W CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/14/1999 - C.S. File 66/12-22

-
- Found - 2½" brass cap on a 1½" O.D. by 36" long iron pipe is
found out of position on top of ground. 1961
1½" O.D. iron pipe, flush with ground. 1922?
¾" GLO brass cap on a 3" OD by 36" long iron pipe
out of position on top of ground. 1924
12" now 21" dia., 2 ft. high D.Fir stump with a
fully healed blaze, good scribing found bears
S.29½°E., 63.6 ft. (rec. S.28½°E., 99.7 ft. goes
to a 1961 DSCO position that was probably set in
error)
6" now 22" dia., 2 ft. high Cedar stump good
scribing found bears N.13½°E., 105.5 ft. (rec.
N.31½°E., 82.7 ft. goes to a 1961 DCSO corner
position that was probably set in error) 1961
No BTs from 1924 found.
- Set - Reset 1961 DCSO BC/IP at the position determined by
ties to GLO BC/IP to the West & M71-8 I.R.
Northerly. Brass cap stamped "RESET 1999"
- BOs - 1924 GLO BC/IP (TR 63 AP 4, AP 1 TR 47) DCSO RESET
1999, bears S.88 ¾°E., 65.3 ft (Agrees well
with 1924 rec.)
1½" O.D. iron pipe flush w/ground bears N.82°W.,
10.8 ft. from M 1-2.
5/8" IR bears N.17½°E., 226.5 ft. (Agrees w/Calc.
rec.) M71-8
1924 GLO BC/IP (TR 63 AP 3, TR 47 AP 2) bears N.88
¾°W., 96.4 ft. (Agrees well with 1924 rec.)
9" dia., Madrone double blazed and scribed "X CS BT"
bears N.84½°W., 36.7 ft.

Area around corners appears to have been bull dozed several
times in past.

See sketch in file.

See next page for calculations used in setting this corner.

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Tsp. Corner (Sec 6)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

