

PRIMARY CORNER DESCRIPTION SW 1/16 Sec. 30

Alias <u>927010</u>	Description <u>Cor. #1 Tract 55</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch , U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO records Vol. 14 Page(s) 6001)

Point for SW 1/16 cor. of original sec. 30.
Set an iron post, 3' long, 1" dia., 28" in the ground, for cor. #1 of this survey, with brass cap mkd:

S30
AP 1 | SW 1/16
TR 55 |
1924

from which

A laurel, 34" dia., bears S.74°W., 53 lks., mkd: "A P 1 TR 55 BT".

Fd. Brass Cap by Howard Johnstone, Feb. 11, 1963, M 24-62

BLM resurvey by Wayne Rogers, under Group #1454. Surveyed Aug. 1988/ May 1989 (DCSO records Vol. 49 Page(s) 18741)

Found 1924 brass cap properly marked, projecting 7" above ground, from which Mensch's BT

A madrone, 38" dia., bears S.74°W., 53 lks., with partially healed decayed blaze, no scribe marks remain. and a new BT

A fir, 8" dia., bears S.36½°W., 95 lks., mkd: "AP1 55 TR55 BT".

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2072, surveyed Aug. 2006 (DCSO rec. Vol. 55 pg(s) 21427)

The Cor. No. 1, Tract 55, monumented with an iron post, 1" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.

from which a bearing tree mkd. by Mensch

A madrone, 27" dia., bears S.74°W., 35.0 ft., with a healed blaze.

and a bearing tree mkd. by Rogers

A fir, 10" dia., bears S.36½°W., 62.7 ft., with a healed blaze.