

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 120400

PRIMARY CORNER DESCRIPTION West 1/16 Cor. Secs. 18 & 19

Alias 924020 Description SE Cor. Tract #52 (Cor #4)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Mensch under Instructions dated April 18, 1924  
(DCSO records Vol. 14 Page(s) 5951-52)

-----  
Point for W 1/16 sec. cor. bet. secs. 18 and 19; identical  
with cor. No. 4 of Tract No. 52.

Set an iron post 3 ft. long, 1" dia., 28" in the ground, for  
cor. No. 4 of Tract No. 52, with brass cap marked:

TR 52		
AP 4		S18
		S19
		W 1/16
		1924

from which

A W.Oak 10" dia., bears N.44°W., 42 lks. dist., marked A  
P 4 TR 52 B T.

Douglas Co. Surveyors Office - Gary Langlitz; L.E. Monrean;  
P. Earle; K. Cheney; Vic Cangie; Mike Tompkins - Feb. 2, 1977  
C.S. File 59/29-21

-----  
Found - 1924 GLO brass cap properly stamped, 27" above  
ground.

Remains of rotten Oak, size indeterminate, dislodged  
and laying downhill from orig. position. The  
base of the trunk bears N.36½°W., 27.7 ft. (Rec.  
N.44°W.) No scribing found.

As cap is 27" above ground, I reference position of monument  
and relocate it 4" above ground at the exact point where  
found and referenced.

New BTs -A 17" D.Fir bears S.32½°W., 21.9 ft. Tree double  
blazed and scribed "W 1/16 S19 CS BT".

A 12" D.Fir bears N.4½°W., 48.1 ft. Tree double  
blazed and scribed "AP 4 Tr 52 CS BT".