

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 120420

PRIMARY CORNER DESCRIPTION SW 1/16 Cor. Sec. 18

Alias 924010 Description NE Cor. Tr. #52 (Cor. #1)  
Alias 923020 Description SE Cor. Tr. #51 (Cor. #4)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Mensch under Instructions dated April 18, 1924  
(DCSO records Vol. 14 Page(s) 5995)

-----  
Point for SW 1/16 sec. cor. of original sec. 18.  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for  
cor. No. 4 of this survey, identical with cor. No. 1 of Tract  
No. 52, with brass cap marked:

TR 51		
AP 4		SW 1/16
AP 1		
TR 52		S18
		1924

from which

- A Fir 12" dia., bears N.39°W., 20 lks. dist., marked AP 4  
TR 51 BT.
- A B.Oak 24" dia., bears S.83°W., 20 lks. dist., marked AP  
1 TR 52 BT.

Douglas Co. Surveyors Office - Gary Langlitz; K.Cheney;  
P.Earle; S.Flause - May 10, 1977 - C.S. 59/34-13 & RM 3-8

-----  
Found - 1924 GLO brass cp with 1" I.P., 8½" above ground,  
properly mkd.

- A 12" Fir now a 15" Fir snag, bears N.39°W., 13.2  
ft. Healed over blaze. We chopped into Fir,  
found scribing "BT"
  - A 24" B.Oak, down and rotted, bears S.83°W., 13.2  
ft. No visible scribing.
- New BTs -A 10" D.Fir bears S.74°E., 22.5 ft. scribed "SW 1/16  
S18 CS BT" in double blaze.  
A 6" P.Pine bears S.34°W., 15.9 ft. scribed "AP 1  
Tr. 52 CS BT" in double blaze.