

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 120440

PRIMARY CORNER DESCRIPTION Center W. 1/16 Cor. Sec. 18

Alias 922020 Description SE Cor. Tr. #50 (Cor. #4)  
Alias 923010 Description NE Cor. Tr. #51 (Cor. #1)  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Mensch under Instructions dated April 18, 1924  
(DCSO records Vol. 14 Page(s) 5993-94)

-----  
Point for W 1/16 sec. cor. of original sec. 18.  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for  
cor. No. 4 of this survey, identical with cor. No. 1 of Tract  
No. 51, with brass cap marked:

TR 50	
AP 4	W 1/16
AP 1	
TR 51	S18
1924	

from which

A Maple 7" dia., bears S.29½°W., 65 lks. dist., marked A  
P 1 TR 51 BT.

A Fir 22" dia., bears N.25°W., 49 lks. dist., marked AP 4  
TR 50 BT.

Douglas Co. Surveyors Office - Rod Kimberling; K. Cheney; S.  
Flause - May 16, 1977 - C.S. File 59/34-18 and RM 3-8

-----  
Found - 1" I.P. with brass cap, GLO survey 192 marked. (We  
could not read the year digit) Should read 1924.  
Brass cap is 7" above ground, 8 ft. East of dry  
channel in clearcut, 50 ft. South of tree line.  
Remains of Maple stump bears S.29½°W., 42.9 ft. Size  
indeterminate. No scribing found.

A 26" Fir stump bears N.22°W., 31.5 ft. (Rec.  
N.25°W., 49 lks.) Opened healed over blaze,  
found scribing "AP 4 Tr 50 BT".

New BTs -A 9" D.Fir bears S.81°W., 29.2 ft. double blazed and  
marked "AP 1 Tr 51 S18 CS BT".

A 24" I.Cedar bears N.62½°E., 58.2 ft. Double blazed  
and marked "CW 1/16 S18 CS BT".