

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 120500

PRIMARY CORNER DESCRIPTION West 1/16 Cor. Secs. 7 and 18

Alias 921010 Description NE Cor. Tr. #49 (Cor #1)
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Mensch under Instructions dated April 18, 1924
(DCSO records Vol. 14 Page(s) 5948-49)

Point for W. 1/16 sec. cor. bet. secs.7 and 18, and cor. No. 1 of Tract No. 49.

Set an iron post, 3 ft.long, 1" dia., 28" in the ground, for cor. No. 1 of Tract No. 49, with brass cap marked:

 S7

 AP1 | S18 W 1/16
 TR 49 |
 1924

from which

A Fir 7" dia., bears S.44°W., 39 lks. dist., marked A P 1
TR 49 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz; L.E. Monrean; P.Earle; K.Cheney; Vic Cangie; Mike Tompkins - Jan. 24, 1977 - C.S. File 59/29-14

Found - 1924 GLO brass cap on 1" I.P. firmly set extending 8" above ground properly marked.

from which:

An Orig. 7" now 18" D.Fir, alive and well healed bears S.44°W., 25.7 ft.

New BT - A 7" G.Fir bears S.38½°E., 50.4 ft. scribed "W 1/16 S18 CS BT" on a double blaze.

BLM survey by Daniel Weller and Dale Bedell, under Group #1447 Surveyed, June 1988/Feb. 1989 - (DCSO records Vol. 48 Page(s) 18538)

The W 1/16 sec. cor., identical with Angle Point No. 1 of Tract 49, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground with 1924 brass cap.

from which a bearing tree mkd. by Mensch:

A Fir 24" dia., bears S.44°W., 39 lks. dist., with healed blaze.

and a bearing tree mkd. by Langlitz in 1977:

A Fir 8" dia., bears S.39½°E., 77 lks. dist., with healed blaze.

and a new bearing tree:

A Madrone 26" dia., bears N.24°E., 64 lks. dist., marked W 1/16 S7 BT.