TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6541)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears S.7°E., 51 lks. dist.
A B.Oak 6" dia., bears N.77°E., 38 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5957)

Intersect the point for ¼ sec. cor., located by record bearing and distance from the original SE bearing tree.
At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼ S30 / S31 / 1924
from which the original bearing tree:
A B.Oak 18" dia., bears S.7°E., 51 lks. dist., blazes plain, marks grown over and not opened.
New bearing trees:
A Laurel 32" dia., bears N.61°E., 63 lks. dist., mkd. ¼ S30 BT.
A B.Oak 10" dia., bears S.81°E., 121 lks. dist., mkd. ¼ S31 BT.

Howard Johnstone - For: Roseburg Lumber Co. - Feb. 11, 1963 - M 24-62

Found - 32" Laurel, N.61°E.,42.2 ft.
Also found brass cap.
Scribed -16" Fir S.55°E., 19.4 ft.