

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6544)

Set ¼ sec. post, at average distance, from which
A Laurel 6" dia., bears S.20°W., 11 lks. dist.
A Laurel 6" dia., bears N.58°E., 15 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5951)

Intersect the point for ¼ sec. cor., located by record bearing and measurement from the NE bearing tree.
At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec.cor., with brass cap marked:
$$\frac{1}{4} \begin{array}{r} S 18 \\ S 19 \\ 1924 \end{array}$$

from which the original bearing tree:
A Laurel snag bears N.58°E., 15 lks., old blazes show.
New bearing trees:
A Chinquapin 12" dia., bears N.53°E., 49 lks. dist., mkd. ¼ S18 BT.
A Laurel 10" dia., bears S.21°E., 14 lks. dist., mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell; Dale McFarland - June 1962 - C.S. File 49/139-78

Found - 1924 GLO brass cap and NE BT., shows good scribing.
SE BT, now down.
New BT - 8" Red Fir N.85°W., 10.6 ft. scribed ¼ S19 CS BT.

Fd. OK, DCSO, L. Monrean, Feb. 2, 1977, C.S. File 59/29-20

BLM survey by Weller and Bedell under Group #1447 Surveyed, June 1988/Feb. 1989 (DCSO records Vol. 48 Page(s) 18537)

Found ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 7" above ground, with 1924 brass cap. from which the remains of the bearing trees mkd. by Mensch:
A chinquapin 20" dia., bears N.54°E., 49 lks. dist., with healed blaze. (Rec. N.53°E.)
A root hole bears S.21°E., 14 lks. dist., with a down Madrone alongside, 13" dia., with healed blaze.
and a bearing tree mkd. by Byron in 1962:
A Fir 14" dia., N.89½°W., 32 lks., with healed blaze.