

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Douglas Co. Surveyors Office - Ben B. Irving; N.E. Richardson July/Aug. 1947 - C.S. File 38/188 and M 6-14</p> <p>-----</p> <p>Set 1" x 36" Iron Pipe. Bearing trees: 26" Cedar, N.86°W., 27.6 ft. 40" Fir S.2°W., 39.0 ft.</p>
<p>Glenn Baughman - For: Carl Summerlin - July 1973 - C.S. File 55/306 and M 50-11</p> <p>-----</p> <p>Found - 1" I.P. with a 2" Angle iron welded on side. 30" Cedar bears S.87°W., 29.4 ft. visible scribing C ¼ S7 BT.</p> <p>This corner was erroneously set by survey M 6-14. Set 2" I.P. with brass cap mkd: C ¼ Sec. 7 T29S R7W W.M. New BTs -6" D.Fir bears N.45°E., 11.3 ft. scribed C¼ S7 BT 8" D.Fir bears S.42°E., 19.7 ft. scribed C¼ S7 BT</p>
<p>BLM survey by Weller and Bedell, under Group #1447, Surveyed, June 1988-Feb. 1989 - (DCSO records Vol. 48 Page(s) 18539-40)</p> <p>-----</p> <p>The center ¼ sec. cor. of sec. 7, established by Glen Baughman in 1973, and is accepted as the corner; monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap mkd: T 29 S R 7 W SEC 7 C ¼</p> <p>OLS 536</p> <p>from which bearing trees mkd. by Baughman: A Fir 11" dia., bears N.38½°E., 18 lks. dist., with healed blaze. A Fir 11" dia., bears S.46°E., 30 lks. dist., with healed blaze.</p> <p>From this point, a point established by N.E. Richardson in 1947, bears S.86°30'W., 0.26 chs. dist., monumented with an iron post 1" dia., with a 2" angle iron welded to the side, firmly set, projecting 2" above ground, from which a bearing tree mkd by Richardson: A Cedar 36" dia., bears S.87°W., 45 lks. with healed blaze Subsequent private surveys after 1947 found this point to be erroneously set and did not accept it.</p>
<p>Fd. OK by M. Heimbürger, June 1999 - M131-67</p>
<p> </p>