

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

BLM survey by Daniel Weller and Dale Bedell under Group #1447, Surveyed, June 8, 1988-Feb. 17, 1989 (DCSO records Vol. 48 Page(s) 18540-41)

The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap mkd:

1/4 $\frac{S\ 6}{S\ 7}$
1924

from which a bearing tree mkd. by Baughman, LS #536, in 1973, An Ash 6" dia., bears S.1 1/4°W., 280 lks. dist., with scribe marks 1/4S BT visible on partially healed blaze.

and a new bearing tree:

A Scotch Pine 6" dia., bears S.10 1/2°E., 158 lks. dist., mkd. 1/4 S7 BT.

The corner is located in a Christmas tree farm with no suitable trees available within limits in sec. 6

DCSO-GIS Corner visitation - 1/25/2001 - Typed: 2/2/2011 - C.S. File 67/33-1

Monument - BC/IP

Found OK by K. DeGroot, Aug. 2004 - M145-44

Fd. as per renewal by N. Hibbs, 1/2013 - M157-69