TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6540)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.52°E.,12 lks. dist.
A Laurel 4" dia.,bears S.76°W., 13 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5958)

Proportionate distance.
Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. with brass cap marked: ¼
S31 | S32
1924
from which
A B.Oak 16" dia., bears S.76°E., 41 lks. dist., marked ¼ S32 BT.
A Pine 44" dia., bears S.61°W., 37 lks. dist., marked ¼ S31 BT.

Douglas Co. Surveyors Office - James W. Bryon, Deputy - Dale McFarland; John Powell - May 1962 - C.S. File 49/139-64

Found - Brass cap at corner.
B.Oak to SE, down.
Pine to SW, now stump, shows small scribe mark at top of cut.
New BTs -24" Laurel bears S.65½°E., 45.6 ft. scribed ¼ S32 CS BT.
5" Chinquapin bears N.64°W., 14.0 ft. scribed ¼ S31 CS BT.

Ted Baker, Roberts Surveying - For: Seneca Jones Timber Co. - Oct. 2000 - M 136-9 A & B

Found - 1924 GLO Brass cap.
10" Chinquapin, N.64°W., 14.0 ft. (scar vis)
26" Laurel snag, S.65½°E., 45.6 ft.
New BT - 10" Fir, S.3°E., 3.1 ft.
Note - All new BTs are scribed & painted red. Distances to BTs are center measured.