

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6540)

Set post corner of secs. 29, 30, 31 and 32, from which
A B.Oak 16" dia., bears S.29°E., 43 lks.
A B.Oak 17" dia., bears N.45°E., 90 lks.
A B.Oak 20" dia., bears N.4°W., 56 lks.
A Pine 18" dia., bears S.64°W., 37 lks.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5956)

Intersect the point for sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for sec. cor., with brass cap marked:

T29S	R7W
S 30	S 29
S 31	S 32
1924	

from which the original bearing trees:

A B.Oak 24" dia., bears S.26°E., 43 lks. dist., (not S.29°E.) marks grown over.

A B.Oak 36" dia., bears N.4°W., 48 lks. dist., (not 56 lks.), marks grown over.

A B.Oak stump hole, bears N.45°E., 90 lks. dist.

A Pine stump hole bears S.64°W., 37 lks. dist.

New bearing trees:

A Laurel 10" dia., N.75°E., 28 lks. mkd. T29S R7W S29 BT.

A Laurel 12" dia., S.82°E., 28 lks. mkd. T29S R7W S32 BT.

A Fir 6" dia., bears S.19°W., 7 lks. mkd. T29S R7W S31 BT.

A Laurel 14" dia., bears N.70°W., 66 lks. mkd. T29S R7W S30 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - May 1962 - C.S. File 49/139-65

Found - Brass cap at corner. All BTs gone. Corner checks call to old road. This area cleared and burned years ago.

New BTs -5" Fir bears N.14°W., 13.5 ft. scribed S30 CS BT T29

8" Laurel bears N.53°E., 10.7 ft. scribed S29 CS BT T29S R7W

7" R.Fir bears S.69°E., 25.5 ft. scribed S32 CS BT.

5" Laurel bears S.88°W., 22.8 ft. scribed S31 CS BT.

