

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6541)

Set ¼ sec. post, from which
A Pine 36" dia., bears S.61°W., 69 lks. dist.
A B.0k 14" dia., bears N.87½°E., 109 lks.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5955)

Intersect the point for ¼ sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec.cor., with brass cap mkd.

¼
S30|S29
1924

from which the original bearing trees;

A B.0ak 30" dia., bears N.82½°E., 109 lks. dist., (Not N.87½°E.), marks grown over.

A Pine stump, 40" dia., bears S.60°W., 69 lks. dist. (not S.61°W)

New Bearing trees:

A Pine 30" dia., bears S.43°E., 65 lks. dist., mkd. ¼ S29 BT.

A Laurel 12" dia., bears S.11½°W., 86 lks. mkd. ¼ S30 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Dale McFarland - May/June 1962 - C.S. File 49/139-75

Found - Brass cap set in 1924 and Laurel BT bearing S.11½°W., 86 ft. (OK). 30" Pine gone.

New BT - 9" Fir N.89°E., 18.4 ft. mkd. ¼ S29 CS BT.

Mark Smalley, Roseburg Resources - Bill Olson, Party Chief - Mike Fromdahl, witness - 9/8/2003 - C.S. File 65/48-23

Found - 1924 GLO IPBC (properly marked)

8" Fir S.32°W., 16.9', healed face.

14" Laurel S.11½°W., 56.8' (5' tall stob)

9" Cedar N.27°W., 25.3', scribe visible.

10" Cedar N.25°W., 40.0', scribe visible.

30" B.0ak stump, N.82½°E., 71.9' (under Blackberry bush) Orig.

New BTs- 7" Fir S.34°E., 21.8', scribed "¼ S BT"

24" Fir N.56°W., 35.0', scribed "¼ S BT"