

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6541-42)

Set post corner of secs.19, 20, 29 and 30, from which
A Laurel 4" dia., bears S.48°E., 14 lks. dist.
A Laurel 4" dia., bears N.72°E., 12 lks. dist.
A Laurel 8" dia., bears N.86°W., 24 lks. dist.
A Laurel 4" dia., bears S.83°W., 25 lks. dist.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5953)

Proportioned distance bet. ¼ sec. cor. of secs.19 and 20 and ¼ sec. cor. bet. secs. 29 and 30, and on meridional line of Ford's blazes.

Set an iron post, 3 ft. long, 2" di., 28" in the ground, with brass cap marked:

T29S	R7W
S19	S20
S30	S29
1924	

from which

- A Fir 10" dia., bears N.38°E., 17 lks. dist., marked T29S R7W S20 BT.
- A Fir 18" dia., bears S.65°E., 38 lks. dist., marked T29S R7W S29 BT.
- A Fir 12" dia., bears S.23°W., 26 lks. dist., marked T29S R7W S30 BT.
- A Fir 12" dia., bears N.17°W., 37 lks. dist., marked T29S R7W S19 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - June 1962 - C.S. File 49/139-75

Found - Brass cap and BTs set in 1924 as follows:

- 10" Fir N.38°E., 17 lks. Down.
- 18" Fir S.65°E., 38 lks. OK.
- 12" Fir S.23°W., 26 lks. OK.
- 12" Fir N.17°W., 37 lks. OK.

New BT - 14" Fir N.68¼°E., 17.7 ft. mkd. T29S R7W S20 CS BT.

Corner Fd. OK, BLM survey by Weller and Bedell, 1988-89 (DCSO records, Vol. 48 Pgs. 18532-33)

FD. Ok by Mark Smalley, 9/8/2003 - C.S. File 65/48-22

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: Roseburg Resources - 6/2014 - M166-11

Found - A 2" iron post by Mensch in 1924, firmly set, projecting 1" above ground, with a 2½" brass cap properly mkd. From which BTs by Mensch:

A 24" D.Fir bears record S.65°E., 25.1 ft with healed dbl blaze.

A 14" D.Fir broken snag bears record S.23°W., 17.2 ft with healed dbl blaze

A 15" D.Fir bears record N.17W., 24.4 ft with healed dbl blaze

A BT by DCS0 per CS 49/139:

A 24" D.Fir bears N.68°15'E., 17.7 ft with healed dbl blaze

New BT - A 26" D.FIR BEARS S.44°W., 36.8 ft scribed "T29S R7W S30 BT"