

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6543)

Set ¼ sec. post, from which
A Fir 8" dia., bears S.77°E., 11 lks.
A Fir 10" dia., bears S.64°W., 6 lks.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5952)

Intersect the point for ¼ sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap mkd:

¼
S19|S20
1924

from which the original bearing trees:

A Fir 16" dia., bears S.77°E., 11 lks. dist. marks grown over and not opened.

A Fir 22" dia., bears S.68°W., 6 lks. dist. (not S.64°W.) marks grown over and not opened.

New bearing trees:

A Fir 18" dia., bears S.35°E., 23 lks. mkd. ¼ S20 BT.

A Fir 18" dia., bears N.86°W., 28 lks. mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland and John Powell - June 1962 - C.S. File 49/139-70

Found - Brass cap at corner and on North bank of creek.

Both 1924 BTs gone. We find 24" Fir stump that checks bearing and distance for orig. SW BT.

New BT - 13" R.Fir bears N.16°W., 34.0 ft. scribed ¼ S19 CS BT.

Douglas Co. Surveyors Office - Larry Monrean, Deputy - K. Cheney; P.L. Earle - Jan. 10, 1977 - C.S. File 59/29-4

Found - 1924 GL0 brass cap properly stamped, attached to a 1" x 36" I.P., approx. 18" above ground.

Orig. 10" Fir now 23" stump bears S.64°W., 4.6 ft. (rec. 4.0 ft.) I do not open for scribing.

Orig. SE BT is gone.

A Red Fir 13" now a dead snag 15" bears N.14½°W., 34.8 ft. (Rec. N.16°W., 34.0 ft.) Tree double blazed, scribing visible "S19 CS BT".

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

As monument is 18" above ground and slightly loose, I reference position of cap and lower it to approx. 6" above ground at the referenced position.

New BT - 18" Cedar bears N.17½°W., 35.2 ft. Tree double blazed and scribed "¼ S19 CS BT".

This corner falls near North edge of creek bed, (creek re-routed by beaver dam) and on South edge of road.

There are no trees suitable for scribing in Sec. 20.

BLM resurvey by Daniel Weller and Dale Bedell under Group #1447 - Surveyed June 1988/Feb. 1989 (DCSO records Vol. 48 Page(s) 18535)

The ¼ sec. cor. monumented with an iron post, 1" dia., firmly set, projecting 6" above ground with brass cap mkd: ¼ S19 S20 1924.

from which the remains of an original bearing tree:

A rotted Fir stump 18" dia., bears S.68°W., 6 lks. dist., with weathered face.

and the remains of a bearing tree mkd. by James Byron, 1962:

A Fir snag 13" dia., bears N.17¼°W., 51½ lks. dist., with scribe marks S19 CS BT visible on partially healed double blaze.

and a bearing tree mkd. by Langlitz in 1977:

A Cedar 21" dia., bears N.20¼°W., 54 lks. with scribe marks ¼ C BT visible on partially healed double blaze.

and a new bearing tree:

A Fir 11" dia., bears S.78¼°E., 93 lks. mkd. ¼ S20 BT.

From this point, the Douglas County Surveyors Office triangulation station "OLALLA", bears S.66°57'10"E., 67.103 chs. dist.

Mark Smalley - For: Roseburg Forest Products - Oct. 4, 1993 - C.S. File 63/153-39

Found - Iron pipe with 1924 BLM Brass cap.

Fir stump, poor condition, bears S.68°W., 6 lks.

21" Cedar, N.20¼°W., 35.2 ft. - tall stump, tag nailed to top of stump.

13" Fir snag, N.17¼°W., 34.0 ft. - tall stump, tag nailed to top of stump.

13" Fir, S.78¼°E., 93 lks - good - healed face

New Accessories -

10" Fir, N.4°E., 30.0 ft. scribed "¼ BT"

12" Fir, N.6°E., 31.0 ft. scribed "¼ BT"

11" Alder, S.80°E., 28.6 ft. scribed "¼ BT"

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: Roseburg Resources - 6/2014 - M166-11

Found - A 1" iron post by Mensch in 1924, firmly set in south road shoulder, projecting 6" above ground and leaning southerly, with a 2 1/2" brass cap properly mkd. I return to plumb position. Accessories per CS 63/153 by Smalley in 1993.