

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200460

PRIMARY CORNER DESCRIPTION North 1/16 for Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Gary L. Langlitz; L.E. Monrean
P.E. Earle - S.J. Flaue - (Berry Creek Dam Project) Oct. 4,
1977 - C.S. File 59/40-31 and RM 3-8

No monuments or accessories found.
Location determined by single proportionate measurement.
Set 3/4" x 24" I.P. flush in the ground on a moderate
westerly slope, with anchor rod extended and brass cap
marked:

Douglas County Surveyor

N 1/16

S 18 | S 17

T 29 S R 7 W

1977

BTs - A 15" D.Fir double trunked, double blazed and scribed
"N 1/16 S18 CS BT" bears N.79°W., 55.2 ft. to center
of root crown.

A 20" W.Oak scribed "N 1/16 S17 CS BT" on a double
blaze bears N.34°E., 146.7 ft.

Corner location approx. 3 ft. North of an E-W fence line in
a natural opening. We place steel fence post with survey
marker witness sign 1 ft. North of the corner.

Fd ok by BLM dependent resurvey by Bryan S. Seibold,
Cadastral Surveyor, and Robert Browning, Surveying
Technician, under Group #1745, surveyed Aug. 1994 thru
April. 1995 - (DCSO records Vol. 52 Page(s) 20072)