

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6545)

Set a post cor. of secs. 7, 8, 17 and 18, from which
A B.Oak 14" dia., bears S.72°E., 59 lks. dist.
A B.Oak 9" dia., bears N.43½°E., 72 lks. dist.
A B.Oak 24" dia., bears N.42°W., 8 lks. dist.
A B.Oak 8" dia., bears S.66°W., 68 lks. dist.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5947)

Intersect the point for sec. cor., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for sec. cor., with brass cap mkd:

T29S	R7W
S7	S8
<hr/>	
S18	S17
1924	

from which the original bearing trees:

A B.Oak 18" dia., bears N.44½°E., 72 lks. (not N.43½°E.) blazes are plain.

A B.Oak 24" dia., bears S.69½°E., 59 lks. (not S.72°E.), blazes and marks plain.

A B.Oak 16" dia., bears S.66°W., 68 lks. blazes plain.

A B.Oak 40" dia., bears N.42°W., 8 lks. dist. marks are plain.

New Bearing trees:

A Fir 14" dia., bears N.29°E., 52 lks. dist. mkd. T29S R7W S8 BT.

A Fir 10" dia., bears S.88½°E., 72 lks. dist., mkd. T29S R7W S17 BT.

A Fir 30" dia., bears S.67°W., 40 lks. dist., mkd. T29S R7W S18 BT.

A B.Oak 30" dia., bears N.24°W., 42 lks. dist., mkd. T29S R7W S7 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - May/June 1962 - C.S. File 49/139-77

Found - Brass cap at corner and stump of SW BT, shows scar. SE & NE BTs down. NW BT, not found.

New BTs -10" R.Fir bears S.59°E., 17.5 ft. scribed S17 T29S R7W CS BT.

4" R.Fir bears N.40½°E., 21.6 ft. scribed S8 CS BT.

9" R.Fir bears S.9°W., 33.5 ft. scribed S19 T29S R7W CS BT. No trees near to NE.

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____


Douglas Co. Surveyors Office - Gary Langlitz, Deputy - P.L. Earle; Karen Cheney; Vic Cangie; Mike Tompkins - Jan. 13, 1977 - C.S. File 59/29-10

 Found - 1924 GLO brass cap firmly set and properly stamped.
 10" Fir now an 11" stump, bears S.88½°E., 47.5 ft. scribing "7W S17 BT" visible on rotted face.
 30" Fir now 36" stump, bears S.67°W., 26.4 ft. We open and find scribing "R7W" visible.
 10" now 18" D.Fir bears S.59°E., 17.5 ft. healthy and shows double blaze.
 4" now 12" D.Fir bears N.40½°E., 21.6 ft. Tree is alive and shows faint double blaze.
 9" now 15" D.Fir bears S.9°W., 33.5 ft. Tree is alive and shows good double blaze.
 We find no other evidence.
 New BT - A 7" D.Fir bears N.65°W., 28.7 ft. mkd. "T29S R7W S7 CS BT" in a double blaze.

Fd. OK, Dec. 1990, M 111-17

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1745, surveyed Aug. 1994 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20073)

 The cor. of secs. 7, 8, 17 & 18, monumented with an iron post, 2" diam., firmly set, projecting 8" above ground, with brass cap mkd.



from which the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1962

A fir, 19" diam., bears N.40¼°E., 32½ lks., with healed double blaze.

A fir, 25" diam., bears S.61½°E., 26 lks., with healed double blaze.

A sawed fir stump, 18" diam., bears S.8¼°W., 50½ lks., with healed double blaze.

and a bearing tree mkd. by Gary L. Langlitz, Deputy County Surveyor, in 1977

A fir, 13" diam., bears N.62 3/4°W., 42½ lks., with healed double blaze.

and a new bearing tree

A fir, 9" diam., bears S.9°W., 17½ lks., mkd. T29S R7W S18 BT.

CONT.

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Adam DeGroot - For: Rodney James - Jan. 2020 - M176-36

Found - A 2" dia. USGLO iron post, by Mensch in 1924, firmly set and projecting 8" above ground, with a 2½" brass cap properly mkd. per the record.

From which the remains a BT by Mensch in 1924:

A 36" rotted fir stump bears S.67°30'W., 26.8 ft w/no mks. vis. (S.67°W., 40 lks) 1924 (S.67°W., 26.4') 1977

And BTs by Byron in 1962:

A 26" D.Fir bears N.39°15'E., 21.5 ft w/healed dbl blaze (N.40½°E., 21.6') 1962 & 1966 (N.40¼°E., 32.5 lks) 1994/1995

A 33" D.Fir bears S.62°45'E., 17.1 ft w/healed dbl blaze (S.59°E., 17.5') 1962 & 1977 (S.61½°E., 26 lks) 1994/1995

And a BT by Langlitz in 1977:

A 17" D.Fir bears N.63°30'W., 28.3 ft w/healed dbl blaze (N.65°W., 28.7') 1977 (N.62¾°W., 42.5 lks) 1994/1995

And a BT by Seibold in 1995:

A 17" D.Fir bears S.8°45'W., 11.4 ft w/healed blaze (S.9°W., 17.5 lks) 1994/1995

NAD 83 (2011) EPOCH 2010.00 GEODETIC COORDINATES:

LAT: 43°03'27.84112N LONG: 123°33'44.80329W