

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6546)

Set 1/4 sec. post, at average distance, from which
A W.Oak 36" dia., bears S.58 1/2°W., 296 lks. dist.
A W.Oak 30" dia., bears S.79°E., 196 lks. dist.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5946)

Apportioned Distance.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap mkd:
S 7 | S 8
1924

from which
A W.Oak 18" dia., bears S.12°E., 123 lks. dist., marked 1/4 S8 BT.
A W.oak 28" dia., bears S.20°W., 151 lks. dist., marked 1/4 S7 BT.

Douglas Co. Surveyors Office - Ben B. Irving; N.E. Richardson - July/Aug. 1947 - C.S. File 38/188 - M 6-14

Found and reset Govt. Iron pipe with brass cap 1" x 36" marked 1/4 S7 S8 1924.
BTs - Stump of old BT, W.Oak, S.20°W., 99.7 ft.
W.Oak, old BT, S.12°E., 81.2 ft.
24" W.Oak, New BT, 114.8 ft., S.14°W.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell Dale McFarland - June 1962 - C.S. File 49/139-84

Found - Brass cap at corner, 8" under surface. SE BT now stump. SW BT is OK, shows good scars.
28" W.Oak bears S.50°E., 156.0 ft. We do not scribe this tree.
Set 3/4" Iron rod South, 23.8 ft. from corner and under East-West fence.

Corner tied and used in BLM survey by Weller and Bedell in survey dated June 1988-Feb. 1989 (DCSO records, Vol. 48 Page 18541)

Fd. OK, Dec. 1990, M 111-17

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/22/2001 - C.S. File 66/19-15

Found - 1924 GLO brass cap/iron pipe 8" below ground. 2 ft.
tall metal witness post 0.5 ft. north of BC/IP.
24" now 24" dia., 2 ft. tall rotted Oak stump bears
S.14°W., 114.8 ft. (1947)
3/4" I.R. in old east-west fence line, protrudes 4"
out of ground bears S.1½°E., 23.8 ft. (rec.
South, 23.8 ft.)

No other BTs found.
New - 1982 Power pole # " 1 "
119
3
2 L bears S.75°W., 125.8 ft.
SW cor. DLC 39, a 1924 GLO BC/IP bears S.86½°W.,
413.7 ft.
13" dia., Sycamore, not marked, bears S.42½°E.,
139.2 ft.
No trees available.
Compass decl. 17 3/4°E.