

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6546)

Set post cor. of secs. 5, 6, 7 and 8, from which
B.Oak 24" dia., bears S.34°E., 104 lks. dist.
B.Oak 30" dia., bears N.40°E., 100 lks. dist.
B.Oak 30" dia., bears N.39°W., 179 lks. dist.
B.Oak 36" dia., bears S.65°W., 69 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5944)

Intersect the point for sec. cor, located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for sec. cor., with brass cap marked:

T29S R7W
S 6*S 5
S 7*S 8
1924

from which old bearing trees:

- A B.Oak 36" dia., bears N.40°E., 98 lks. (not 100 lks)
- A B.Oak 40" dia., bears S.31½°E., 103 lks. (not S.34°E., 104 lks.)
- A W.Oak 44" dia., bears S.65°W., 67 lks. (not 69 lks.)
- A B.Oak 46" dia., bears N.40°W., 177 lks. (not N.39°W., 179 lks.)

Marks are legible on all these trees.

New Bearing trees:

- A Laurel 12" dia., bears N.7°E., 54 lks. mkd. T29S R7W S5 BT.
- A B.Oak 14" dia., bears S.72°E., 8 lks. dist., marked T29S R7W S8 BT.
- A W.Oak 12" dia., bears S.20°W., 2½ lks. dist., marked T29S R7W S7 BT.
- A Fir 12" dia., bears N.29°W., 63 lks. dist., marked T29S R7W S6 BT.

(No record source or date found for this renewal visit. Former Co. Renewal record #2)

New BT - 12" W.Oak S.74°45'E., 22.6 ft.

See M 6-14, 1947 survey

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/22/2001 - C.S. File 66/19-16

Found - 1924 GLO brass cap/iron pipe protrudes 12" out of
ground. Corner is at a fence corner, with old
fence line running N - E & W. A south fence takes
off 25' West of corner.

No old BTs found.

12" now 35" dia., 2½ ft. tall D.Fir stump with a
fully healed blaze bears N.29°W., 41.6 ft. (1924)

12" now 13" dia., W.Oak with a fully healed blaze,
bears S.20°W., 1.7 ft. (1924)

12" now 29" dia., Madrone with a fully healed blaze,
we bark scribe "T29S R7W S5 CS BT" bears N.7°E.,
35.6 ft. (1924)

New - 13" dia., D.Fir double blazed & scribed "T29S R7W S6
CS BT" bears N.86°W., 40.4 ft.

Compass decl. 17 3/4°E.

Fd. as per renewal by N. Hibbs, 1/2013 - M157-69