

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6547)

Set 1/4 sec. post, from which
A B.Oak 6" dia., bears S.13°W., 80 lks. dist.
A B.Oak 8" dia., bears N.82°E., 52 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5943)

Intersect local 1/4 sec. cor. of secs. 5 and 6, which is an Oak post, 4" sq., 12" above ground, firmly set, marked 1/4 S on W. face; from which
A B.Oak 10" dia., bears S.8°W., 4 lks. dist. mkd. 1/4 S BT.
I adopt this cor. which is represented as being in approximate position of the old cor. and appears to be set at intersection of the line of Ford's blazes and the prolongation of the S. bdy. of the McCullough Donation Land Claim, which is on the theoretical center latitudinal subdivision line of sec. 6. I do not alter or disturb this cor. in any way.

Douglas Co. Surveyors Office - James Byron, Deputy - Ray Irving; John Fee - April/May 1955 - C.S. File 46/130

Found - 4" x 4" square stake scribed 1/4 S.
The 10" B.Oak S.8°W., 4 lks. has been cut into and all scribing destroyed. Checks tree for bearing and distance.
Set Brass cap mkd. 1/4 S6|S5 T29S R7W Co. Surveyor Office 1955.
Blazed and scribed:
7" R.Fir N.85°W., 17.0 ft. mkd. 1/4 S6 CS BT.
10" R.Fir S.19°E., 25.4 ft. mkd. 1/4 S5 CS BT.
Corner is 6 ft. West of old wire fence.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/24/2001 - C.S. File 66/19-19

Found - 1955 DCSO Brass cap/iron pipe. Protrudes 14" out of ground. Corner lies 4 1/2 ft. West of a fence corner with fences running N-S & West.
10" now 15" dia., B.Oak with healed scars, bark scribing added to flat portion of healed scar "1/4 S6 CS BT", bears S.8°W., 2.6 ft. 1924
10" now 19" dia., D.Fir with a fully healed double blaze, bears S.19°E., 25.4 ft. (1955)
No other BTs found.

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - 14" dia., B.Oak double blazed & scribed "¼ S5 CS BT"
bears N.24°E., 33.0 ft.
6" dia., D.Fir double blazed & scribed "¼ S6 CS BT"
bears N.40°W., 31.5 ft. {Compass decl. 17 3/4°}