

PRIMARY CORNER DESCRIPTION Sec. Cor. 5 & 6; 31 & 32 of T 28-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 14 Pages 5749-50)

Set post at proper distance, cor. of secs. 5, 6, 31 & 32, from which

- A Laurel 15" dia., bears N.30°E., 25 lks. dist.
- A Laurel 8" dia., bears N.15°W., 100 lks. dist.
- A Red Fir 30" dia., bears S.75°E., 75 lks. dist.
- A B.Oak 10" dia., bears S.43°W., 43 lks. dist.

F.J. Cole, (Cain) for: J.H. Porter - March 5, 1913, Field Book 33 Page 11; C.S. File 5/30 (added 8/26/2011 DCSO JC)

I find original BTs standing. Marking dim I remark Laurel 31" N.30°E., 25 lks.

- A Red (Fir) 54" S.71°15'E., 19 lks. This I remark profing? CS. This tree does not agree with bearings and distance given in original notes.

G.G. Stewart, for: I.B. Nichols - John Cabot; J.B. Howard; C.M. Howard Witness July 8, 1922 - C.S. File 5/28 & M 3-74 - (Added 8/26/2011 DCSO JC)

OBTs do not check with field notes. Evidently turned around. I set rock for cor. from

- 40" Fir S.79°E., 49.5 ft.
- 15" Laurel N.16½°E., 66.0 ft.
- 12" BO. (down) S.31°E., 28.0 ft.

Marked New BTs

- 40" Fir S.79°E., 49.5 ft.
- 36" " S.46°W., 25.0
- 40" " N.24°W., 18.0
- 8" Fir N.34°E., 53.0

J.W. Cole, Co. Surveyor - Witnesses: W.H. Coats; H. Bergh; E. Richardson - Feb. 1923 - Vol. 3 Pgs. 141-147; M 1-2; C.S. File 5/37

Set a flat rock, erected mound of rock, marked with an X with a rock on top bearing old mark S. T. Flat rock 6" x 12" x 18" from which original BTs:

- Laurel with scribe marks rotted off, N.30°E., 16.5 ft.
- Laurel bearing old scribe marks, N.15°W., 66.0 ft.
- Fir BT bearing scars which I did not open, bears S.75°E., 12.0 ft.

Original Oak BT down & decaying, bears S.43°W., 28.4 ft. Corner as set by Gordon Stewart bears N.85°30'W., 36.7 ft.

(See M 3-74; C.S. 5/28) cont.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO retracement by Mensch, 1924 (DCSO records, Vol. 14 Pages 5880-81)

Intersect the point for cor. of secs. 5, 6, 31 & 32, located by measurement from the orig. BTs on which the blazes & some marks are plain. At the exact cor. point:

Set a basalt stone, 20x12x6 ins. 15" in the ground, in a mound of stone, marked with 5 notches on E. and 1 notch on W. edges, from which new bearing trees:

A Maple 12" dia., bears N.53°E., 7 lks. dist., marked
T28S R7W S32 BT.

A Laurel 30" dia., bears S.28°E., 95 lks. dist., mkd.
T29S R7W S5 BT.

A Laurel 16" dia., bears S.4°W., 55 lks. dist., mkd.
T29S R7W S6 BT.

A Fir 12" dia., bears N.23°W., 79 lks. dist., mkd.
T28S R7W S31 BT.

Original bearing trees:

A Laurel 20" dia., bears N.30°E., 25 lks. dist.

A Fir 48" dia., bears S.70°E., 18 lks. dist. (Not S.79°E.,
75 lks. dist.)

A B.Oak 16" dia., bears S.43°W., 43 lks. dist.

A Laurel 16" dia., bears N.15°W., 100 lks. dist.

Doug. County Surveyors Office - B.B. Irving; A.R. Evans,
Deputy Milo Godfrey - for: DeGnath gateway road, Sept/Oct.
1948 C.S. File 39/194; M 22-45

Identified from O.B.T.:

Laurel, N.69°55'W., 16.5 ft., broken and rotting.

48" Fir, N.21°10'E., 11.9 ft., down, scribe marks legible.

Maple, down, BT under log.

BT, S.28°E., broken off, blaze & scribe visible.

Fir, N.24°E., 52 ft., standing, blaze not chopped out.

Laurel, S.4°W., down, scribe marks visible.

Oak, S.43°W., down and rotting.

Set 6 x 8 x 20 inch rock, X on side, on end and made a new mound of rock. Scribe and blazed new BT:

30" Fir, S.83°E., 78.2 ft.

6" Fir, S.80°W., 21.7 ft.

8" Fir S.20°W., 38.9 ft.

24" Fir N.32°E., 54.4 ft.

Doug. County Surveyors Office - James Byron, Deputy - J. Fee;
Ray Irving - May 5, 1955 - C.S. File 46/130

Found - 30" Fir stump S.83°E., 78.2 ft. bark scribed BT.
continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

8" Fir S.20°W., 38.9 ft. some scribing visible. Tree pushed over.
24" Fir stump N.32°E., 54.4 ft. Log against scribing
Set 1" x 30" Iron pipe with brass cap marked:
County Surveyors Office
31*32 28 S
6*5 29 S R 7 W
1954
Chiseled 3" cross on high point of rock 12 feet x 10 feet, 8 ft. high, N.78½°W., 90.7 ft. No trees near.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/20/2001 - C.S. File 66/19-40

Found - 1955 DCSO brass cap iron pipe protrudes 12" out of a mound of stone. In mound we find two marked stones laying flat: An 8"x6"x12" stone with an "X" on top (1923, 1924 & 1948?) and a 4"x6"x12" triangular shaped stone marked with an "X" on top & 5 lines on one side and an "L" on another possible 1922 Stewart stone?
From BC/IP 1922 Stewart corner looked for, stone is gone. Evidence of 3 BT's found:
SE BT gone, SW BT tipped out of ground, NW BT is a stump & NE BT is a rotted stump with visible scribing "BT" these BTs agree well with rec. position of Stewart's corner. (M3-74, is 1922 Stewart survey) Agrees well with 1923 rec. of N.85½°W., 36.7 ft. from orig. corner.
30" now 30" dia., 2 ft. high rotted D.Fir stump, no marks visible bears S.83°E., 78.2 ft. (1948)
24" now 28" dia., 2½ ft. high D.Fir with a healed blaze bears N.32°E., 54.4 ft. (1948)
Chiseled "+" on high point of a 12'x10'x8' high rock bears N.79½°W., 89.3 ft. (Rec. N.78½°W., 90.7 ft.) 1955
No other BTs found.

New - 18" dia., D.Fir double blazed & scribed "T29S R7W S5 CS BT" bears S.64°E., 5.0 ft.
5" dia., D.Fir double blazed & scribed "X CS BT" bears N.67°E., 20.0 ft.
14" dia., D.Fir double blazed & scribed "T29S R7W S6 CS BT" bears S.64½°W., 60.4 ft.
Corner lies South 13 ft. form a fence corner lines run N & SW. **See last Pg for pictures.**

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. 5 & 6; 31 & 32 of T. 28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: Nichols Brothers - 9/2011- M162-71

LAT: 43°05'16.09234"N LONG: 123°33'42.45591"W.
Found a 1955 DCSO BCIP and accessories of record by R. Smith
in 2001, per C.S. 66/19-40.



2001

