

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6542)

-----  
Set ¼ sec. post, from which  
A B.Oak 9" dia., bears S.6°E., 27 lks. dist.  
A Pine 8" dia., bears N.10°E., 36 lks. dist.

Howard Johnstone - For: Gordon McDowell - August 1975 - M 57-76

-----  
Set 5/8" Iron rod with aluminum cap.

Douglas Co. Surveyors Office - Gary Langlitz, Deputy - Mike Tompkins; Vic Cangie - Jan. 10, 1977 - C.S. File 59/29-6

-----  
Found - 5/8" I.R. with alum. cap.  
12" Cedar bears N.20°E., 37.0 ft. scribed ¼ S BT with a Roseburg Lumber Co. tag that reads S.20°W 37.0 ft. to corner.  
A 6" Fir bears S.60°E., 14.4 ft. scribed ¼ S BT with a Roseburg Lumber Co. tag that reads N.63°W., 14.4 ft. to corner.  
Both BTs are single blaze.

At cor. point, We set brass cap mkd: Douglas County Surveyors

T 29 S R 7 W

¼  $\frac{S\ 20}{S\ 29}$   
1977

We place orig. iron rod on the North side of our brass cap.

FD. OK by M. Heimbürger - 1/2007 - M146-52

Kris DeGroot - For: Roseburg Resources - 6/2014 - M166-11

-----  
Found - A 1½" iron post by DCSO in 1977 per CS 59/29, firmly set, projecting 4" above ground, with 2 1/2" brass cap properly mkd per record: from which BTs by Johnstone:

A 17" Cedar bears record N.20°E., 37.0 ft with fully healed single blaze

A 19" D.Fir bears record S.60°E., 14.4 ft with fully healed single blaze

The 5/8" iron rod w/alum cap by Johnstone per M57-76 Lies on NE edge of BCIP.