

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Gary Langlitz, Deputy - L.E. Monrean; P. Earle; Stephen Flause - Oct. 11, 1977 - C.S. File 59/40-38 and RM 3-8

Location of corner determined by intersection of lines from opposite exterior $\frac{1}{4}$ corners.

Set a 1" x 30" I.P., 26" in the ground with brass cap attached marked:

Douglas County Surveyor

T 29 S R 7 W

C 1/4 S 20

1977

BTs - A 34" B.Oak scribed "C $\frac{1}{4}$ S20 CS BT" on a double blaze bears N.38 $\frac{1}{2}$ °W., 23.2 ft.

A 12" D.Fir scribed "C $\frac{1}{4}$ S20 CS BT" on a double blaze bears N.2°E., 45.7 ft.

Located along edge of meadow, approx. 50 ft. East of Berry Creek and approx. 250 ft. South of a house. Placed a steel fence post with survey marker witness sign attached, 1.0 ft. West of corner.

Fd. OK by M. Luttrell, Feb. 1998 - L.P. 1998-0043