

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6544)

Set ¼ sec. post, at average distance, from which
A W.Oak 24" dia., bears N.5°W., 18 lks. dist.
A B.Oak 18" dia., bears S.74°W., 38 lks. dist.

Douglas Co Surveyors Office - Gary Langlitz, Deputy - Stephen Flause; Peter Earle; - June 8, 1977 - C.S. File 59/34-33 and RM 3-8

Corner location determined by single proportionate measurement.
Set 1" x 30" I. Pipe 26" in the ground, with brass cap attached mkd: Douglas County Surveyor
T 29 S R 7 W
¼ $\frac{S 17}{S 20}$
1977

BTS - A 10" W.Oak scribed "¼ S17 CS BT" on a double blaze, bears N.61°W., 21.5 ft.
A 28" I.Cedar scribed "¼ S20 CS BT" on a double blaze bears S.2½°W., 23.6 ft.
Approx. 50 ft. South of a small ravine, course S.50°W.

Fd. OK by BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1745, surveyed Aug. 1994 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20077)